

# ATTESTATION OF CONFORMITY

Issued to: Afore New Energy Technology (Shanghai) Co., Ltd.  
Build No.7, 333 Wanfang Road, Minhang District, Shanghai, China

For the product: Hybrid inverter

Trade name: **Afore**

Type/Model: AF3K-SH, AF3.6K-SH, AF4K-SH, AF4.6K-SH, AF5K-SH, AF5.5K-SH, AF6K-SH

Ratings: See Annex

Manufactured by: Afore New Energy Technology (Shanghai) Co., Ltd.  
Build No.7, 333 Wanfang Road, Minhang District, Shanghai, China

Requirements: EN 62109-1:2010  
EN 62109-2:2011  
EN 62477-1:2012+A1:2017

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no. 6098056.50(A-C)

This Attestation implies that the examined types are in accordance with the standards designated under the Low Voltage Directive (LVD) 2014/35/EU.

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of his production with the specimen tested by DEKRA is not the responsibility of DEKRA.

The CE marking may be affixed on the product if all relevant and effective EC directives are complied with.

Arnhem, 4 March 2021

Number: 6098056.01AOC

DEKRA Testing and Certification (Shanghai) Ltd.

Kreny Lin  
Certification Manager

© Integral publication of this attestation and adjoining reports is allowed

Page 1 of 2



## Annex to 6098056.01AOC

### Ratings of the test product:

Operating temperature range: - 25°C to + 60°C

Protective class: I

Ingress protection rating: IP65

Power factor range (adjustable): 0.9 leading...0.9 lagging

#### AF3K-SH:

PV input: Max. 580 Vdc, MPPT voltage range: 50-550 Vdc, max 20 / 20 A, Isc PV: 26 A / 26 A

Battery: Type: Lithium / Lead-acid, nominal 288Vdc, voltage range: 85-360 Vdc, max charge current: 30 A, max charge power: 6000 W

Output: 230 Vac, 50 Hz, rated 13 A, max 15 A, rated 3000 W, max 3000 VA

#### AF3.6K-SH:

PV input: Max. 580 Vdc, MPPT voltage range: 50-550 Vdc, max 20 / 20 A, Isc PV: 26 A / 26 A

Battery: Type: Lithium / Lead-acid, nominal 288Vdc, voltage range: 85-360 Vdc, max charge current: 30 A, max charge power: 7000 W

Output: 230 Vac, 50 Hz, rated 16 A, max 18.5 A, rated 3600 W, max 3600 VA

#### AF4K-SH:

PV input: Max. 580 Vdc, MPPT voltage range: 50-550 Vdc, max 20 / 20 A, Isc PV: 26 A / 26 A

Battery: Type: Lithium / Lead-acid, nominal 288Vdc, voltage range: 85-360 Vdc, max charge current: 30 A, max charge power: 8000 W

Output: 230 Vac, 50 Hz, rated 17.5 A, max 20 A, rated 4000 W, max 4000 VA

#### AF4.6K-SH:

PV input: Max. 580 Vdc, MPPT voltage range: 50-550 Vdc, max 20 / 20 A, Isc PV: 26 A / 26 A

Battery: Type: Lithium / Lead-acid, nominal 288Vdc, voltage range: 85-360 Vdc, max charge current: 30 A, max charge power: 9000 W

Output: 230 Vac, 50 Hz, rated 20 A, max 23 A, rated 4600 W, max 4600 VA

#### AF5K-SH:

PV input: Max. 580 Vdc, MPPT voltage range: 50-550 Vdc, max 20 / 20 A, Isc PV: 26 A / 26 A

Battery: Type: Lithium / Lead-acid, nominal 288Vdc, voltage range: 85-360 Vdc, max charge current: 30 A, max charge power: 10000 W

Output: 230 Vac, 50 Hz, rated 22 A, max 25.5 A, rated 5000 W, max 5000 VA

#### AF5.5K-SH:

PV input: Max. 580 Vdc, MPPT voltage range: 50-550 Vdc, max 20 / 20 A, Isc PV: 26 A / 26 A

Battery: Type: Lithium / Lead-acid, nominal 288Vdc, voltage range: 85-360 Vdc, max charge current: 30 A, max charge power: 10000 W

Output: 230 Vac, 50 Hz, rated 24 A, max 27.5 A, rated 5500 W, max 5500 VA

#### AF6K-SH:

PV input: Max. 580 Vdc, MPPT voltage range: 50-550 Vdc, max 20 / 20 A, Isc PV: 26 A / 26 A

Battery: Type: Lithium / Lead-acid, nominal 288Vdc, voltage range: 85-360 Vdc, max charge current: 30 A, max charge power: 10000 W

Output: 230 Vac, 50 Hz, rated 26 A, max 30 A, rated 6000 W, max 6000 VA