

Test Verification of Conformity

Verification Number: 230900426SHA-V1

On the basis of the referenced test report(s), sample(s) tested of the below product have been found to comply with the standards harmonized with the directives listed on this verification at the time the tests were carried out. Other standards and Directives may be relevant to the product. This verification is part of the full test report(s) and should be read in conjunction with it <them>.

Once compliance with all product relevant **CE** mark directives are verified, including any relevant e.g. risk assessment and production control, the manufacturer may indicate compliance by signing a Declaration of Conformity themselves and applying the mark to products identical to the tested sample(s).

Applicant Name & Address: Afore New Energy Technology (Shanghai) Co., Ltd.

Building 7, No.333 Wanfang Rd, Minhang District, Shanghai, China. 201112

Product Description: Grid-connected PV inverter

Ratings & Principle See Appendix Characteristics:

BNT030KTL, BNT036KTL, BNT040KTL, BNT050KTL, BNT060KTL Models/Type References:

Brand Name: Afore

Relevant Standards/Directives: IEC 61683:1999

Verification Issuing Office Name & Address: Building No.86, 1198 Qinzhou Road (North), Shanghai 200233, China

Intertek Testing Services Shanghai

Date of Tests: 2023-09-13 to 2024-03-25 Test Report Number(s): 230900426SHA-001

Signature

Name: Max Jin

Position: General Manager

Date: 2024-03-25

This Verification is for the exclusive use of intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, roduct or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This . Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program



APPENDIX: Test Verification of Conformity

This is an Appendix to Test Verification of Conformity Number: 230900426SHA-V1

Ratings:

Ratings:					
	Spec	cifications table	9	1	1
Model	BNT030KTL	BNT036KTL	BNT040KTL	BNT050KTL	BNT060KTL
PV input					
P pv Max(kW)	45	54	60	75	90
Vmax PV (Vdc) (absolute Max.)	1100	1100	1100	1100	1100
Isc PV (absolute Max.) (A)	48 x 2	48 x 3	48 x 3	48 x 3	48 x 4
Max. PV input current / strings (A)	38 x 2	38 x 3	38 x 3	40 x 3	38 x 4
Number MPP trackers	2	3	3	3	4
Number input strings	2/3	2/2/2	2/2/2	2/2/3	2/2/2/2
MPPT voltage range (Vdc)	200-1000	200-1000	200-1000	200-1000	200-1000
Vdc range @ full power (Vdc)	500-850	500-850	500-850	500-850	500-850
AC Grid (output)					
Normal AC Voltage (V _{AC})	3P+N+PE/3P+PE 230/400				
Frequency (Hz)			50		
Normal AC Current (A)	43.5	52.2	58	72.5	87
Max. cont. output current (A)	48	60	65	80	96
Normal Power (kW)	30	36	40	50	60
Rated Apparent Power (kVA)	30	36	40	50	60
Max. cont. Power (kW)	30	36	40	50	60
Max. cont. Apparent Power (kVA)	30	36	40	50	60
Power factor(adjustable)	1.0(-0.8~ +0.8)				
Others	7			///	
Protective class	Class I				
Ingress protection (IP)	IP65				
Temperature (°C)	-25°C to +60°C				
Inverter Isolation	Non-isolated				
Overvoltage category	OVC III (AC Main), OVC II (PV)				

Signature

Name: Max Jin

Position: General Manager

Date: 2024-03-25