



ENERGY STORAGE SYSTEM SOLUTIONS PV SYSTEM SOLUTIONS



Afore New Energy Technology (Shanghai) Co., Ltd.

Building 7, No.333 Wanfang Rd, Minhang District,
Shanghai, China. 201112

T +86-21-54326236

F +86-21-54326136

W www.aforeenergy.com

E info@aforeenergy.com

Standard Version: 20251015




I About Us

Afore is a leading PV inverter provider from China, with more than fifteen years dedicated experience in PV inverter R&D and manufacturing, Afore inverters have been installed in Europe, Australia, China, Sri Lanka, India, Japan, North America and South America, meeting the needs of global users.

We provide single and three-phase high-efficiency PV string inverters for a capacity of 1kW to 110kW, storage inverters (single phase 1-12kW, three phase 3-60kW, split phase 3-9.6kW, AC coupled), energy storage battery series (low voltage wall mounted series, high voltage stackable series) and all-in-one storage products. All of our inverters are integrated with smart monitoring system.

We offer not just good products, but also high-efficient local support to our partners and users throughout the inverter life span. Make sure the customers receive reliable returns by choosing Afore!

I Global Market



I Contents



Energy storage system

Residential and Commercial Storage System

- Page 03-34**
- Single Phase Hybrid Inverter 1-6kW
 - Single Phase Hybrid Inverter 7-12kW
 - Single Phase Hybrid Inverter 8-12kW
 - Three Phase Hybrid Inverter 7-12kW
 - Three Phase Hybrid Inverter 3-15kW
 - Three Phase Hybrid Inverter 3-30kW
 - Three Phase Hybrid Inverter 36-60kW

- Page 39-42**
- Split Phase Hybrid Inverter 3-9.6kW

- Page 15-20**
- Wall Mounted Energy Storage Battery (5.22/10.49/16.07kWh)


- Page 35-38**
- High Voltage Stackable Energy Storage Battery (5.22~41.77kWh)



Single Phase PV String Inverter

Residential System


- Page 43-44**
- Single Phase 1-3kW, Single Phase 3-6kW, Single Phase 7-10kW



Three Phase PV String Inverter

Residential & Small Commercial System

- Page 45-48**
- Three Phase 3-25kW



Three Phase PV String Inverter

Commercial System and Power Plants

- Page 49-52**
- Three Phase 30kW, Three Phase 36-60kW, Three Phase 70-110kW

Single Phase Hybrid Storage Inverter

1-3.6 kW



The Afore AF low voltage series storage Inverters are designed to increase energy independence for homeowners. The power range is from 1kW to 3.6kW, compatible with low voltage (40-60V) batteries.

Energy management is based on time-of-use and demand charge rate structures, which significantly reduce the amount of energy purchased from the public grid.

Thanks for the UPS function (switch time < 10ms), that enables the crucial loads power on during outages. Additionally, under the backup operation mode, the inverter provides you up to 150% peak output overloading.

The Afore energy storage inverter features Smart Electricity Pricing & Automation, an energy management tool based on real-time electricity pricing strategies. It continuously monitors electricity price fluctuations and dynamically adjusts device operation accordingly. Operating 24/7 fully automatically without the need for manual intervention, it helps users optimize their electricity usage and reduce energy costs.



AI EMS
Electricity Pricing
& Automation

Max. 1.5

PV OVERSIZE
1.5 Times PV Oversize

2 MPPT

MPPT CHANNELS
Up to 2 MPPT Channels

<10 ms

UPS FUNCTION
Switch Time < 10ms



PARALLEL
Max.6 Parallel Stacking



INPUT
Support Generator

Support for Time-of-use Optimization

Configurable Operation Modes


AFCI (Optional) & Rapid Shutdown Ready

Build in Anti-feed-in Function



Compact Size and Easy Installation

Smart Monitoring & Remote Firmware Upgrade

For New Storage System:




Optimizing Self-Consumption (on-grid) + Emergency Power Supply(off-grid)



Optimizing Self-Consumption Mode

With home energy storage installed, home owners may also be able to change from a flat rate electricity tariff to a time-of-use tariff. For the areas and regions, where peak shaving can be applied.



Technical Data	AF1K-SL-1	AF1.5K-SL-1	AF2K-SL-1	AF2.5K-SL-1
PV Input				
Max. Input Power (kW)	1.5	2.3	3.0	3.8
Max. PV Voltage (V)	550			
MPPT Range (V)	80 - 500			
Full MPPT Range (V)	80 - 500	90 - 500	120 - 500	150 - 500
Normal Voltage (V)	360			
Startup Voltage (V)	100			
Max. Input Current (A)	18.5 x 1			
Max. Short Current (A)	26 x 1			
No. of MPP Tracker / No. of PV String	1 / 1			
Battery Port				
Max. Charge/Discharge Power (kW)	1.0	1.5	2.0	2.5
Max. Charge/Discharge Current (A)	25	40	50	63
Battery Normal Voltage (V)	51.2			
Battery Voltage Range (V)	40 - 60			
Battery Type	Li-ion / Lead-acid etc.			
AC Grid				
Max Continuous Current (A)	5.0	7.0	10.0	12.0
Max Continuous Power (kVA)	1.0	1.5	2.0	2.5
Nominal Grid Current (A)	4.6 / 4.4	6.9 / 6.6	9.1 / 8.7	11.4 / 10.9
Nominal Grid Voltage (V)	198 to 242 @ 220 / 207 to 253 @ 230			
Nominal Grid Frequency (Hz)	50 / 60			
Power Factor	1 default (adjustable from 0.8 leading to 0.8 lagging)			
Current THD (%)	< 3			
AC Load Output				
Max Continuous Current (A)	5.0	7.0	10.0	12.0
Max Continuous Power (kVA)	1.0	1.5	2.0	2.5
Max Peak Current (A) (10min)	6.9 / 6.6	10.5 / 10.0	13.7 / 13.1	17.3 / 16.6
Max Peak Power (kVA) (10min)	1.5	2.3	3.0	3.8
Nominal AC Voltage L-N (V)	220 / 230			
Nominal AC Frequency (Hz)	50 / 60			
Switching Time (ms)	Seamless			
Voltage THD (%)	< 3			
Efficiency				
CEC Efficiency (%)	97.0			
Max. Efficiency (%)	97.6			
PV to Bat. Efficiency (%)	98.1			
Bat. between AC Efficiency (%)	96.8			
Protection				
PV Reverse Polarity Protection	Yes			
Over Current/Voltage Protection	Yes			
Anti-Islanding Protection	Yes			
AC Short Circuit Protection	Yes			
Residual Current Detection	Yes			
Ground Fault Monitoring	Yes			
Insulation Resister Detection	Yes			
PV Arc Detection	Yes			
Enclosure Protect Level	IP65 / NEMA4X			
AC/DC surge protection	Type II			
General Data				
Dimensions (W x H x D, mm)	370 x 535 x 192			
Weight (kg)	17			
Topology	Transformerless			
Cooling	Natural Convection			
Relative Humidity	0 - 100 %			
Operating Temperature Range (°C)	- 25 to 60			
Operating Altitude (m)	< 4000			
Standby Consumption (W)	< 10			
Mounting	Wall Bracket			
Communication with RSD	SUNSPEC			
Display & Communication Interfaces	LCD, LED, RS485, CAN, Wi-Fi, GPRS, 4G, Sunspec			
Certification & Approvals	NRS097, G98, EN50549-1, C10/C11, AS4777.2, VDE-AR-N4105, VDE0126, IEC62109-1, IEC62109-2, IEC62477-1			
EMC	EN61000-6-2, EN61000-6-3			

Technical Data	AF3K-SL-1	AF3.6K-SL-1	AF3K-SL	AF3.6K-SL
PV Input				
Max. Input Power (kW)	4.5	5.4	4.5	5.4
Max. PV Voltage (V)	550			
MPPT Range (V)	80 - 500			
Full MPPT Range (V)	170 - 500	210 - 500	90 - 500	110 - 500
Normal Voltage (V)	360			
Startup Voltage (V)	100			
Max. Input Current (A)	18.5 x 1		18.5 x 2	
Max. Short Current (A)	26 x 1		26 x 2	
No. of MPP Tracker / No. of PV String	1 / 1		2 / 2	
Battery Port				
Max. Charge/Discharge Power (kW)	3.0	3.6	3.0	3.6
Max. Charge/Discharge Current (A)	80			
Battery Normal Voltage (V)	51.2			
Battery Voltage Range (V)	40 - 60			
Battery Type	Li-ion / Lead-acid etc.			
AC Grid				
Max Continuous Current (A)	14.0	17.0	14.0	17.0
Max Continuous Power (kVA)	3.0	3.6	3.0	3.6
Nominal Grid Current (A)	13.7 / 13.1	16.4 / 15.7	13.7 / 13.1	16.4 / 15.7
Nominal Grid Voltage (V)	198 to 242 @ 220 / 207 to 253 @ 230			
Nominal Grid Frequency (Hz)	50 / 60			
Power Factor	1 default (adjustable from 0.8 leading to 0.8 lagging)			
Current THD (%)	< 3			
AC Load Output				
Max Continuous Current (A)	14.0	17.0	14.0	17.0
Max Continuous Power (kVA)	3.0	3.6	3.0	3.6
Max Peak Current (A) (10min)	20.5 / 19.6	24.6 / 23.5	20.5 / 19.6	24.6 / 23.5
Max Peak Power (kVA) (10min)	4.5	5.4	4.5	5.4
Nominal AC Voltage L-N (V)	220 / 230			
Nominal AC Frequency (Hz)	50 / 60			
Switching Time (ms)	Seamless			
Voltage THD (%)	< 3			
Efficiency				
CEC Efficiency (%)	97.0			
Max. Efficiency (%)	97.6			
PV to Bat. Efficiency (%)	98.1			
Bat. between AC Efficiency (%)	96.8			
Protection				
PV Reverse Polarity Protection	Yes			
Over Current/Voltage Protection	Yes			
Anti-Islanding Protection	Yes			
AC Short Circuit Protection	Yes			
Residual Current Detection	Yes			
Ground Fault Monitoring	Yes			
Insulation Resister Detection	Yes			
PV Arc Detection	Yes			
Enclosure Protect Level	IP65 / NEMA4X			
AC/DC surge protection	Type II			
General Data				
Dimensions (W x H x D, mm)	370 x 535 x 192			
Weight (kg)	17			
Topology	Transformerless			
Cooling	Natural Convection			
Relative Humidity	0 - 100 %			
Operating Temperature Range (°C)	- 25 to 60			
Operating Altitude (m)	< 4000			
Standby Consumption (W)	< 10			
Mounting	Wall Bracket			
Communication with RSD	SUNSPEC			
Display & Communication Interfaces	LCD, LED, RS485, CAN, Wi-Fi, GPRS, 4G, Sunspec			
Certification & Approvals	NRS097, G98, EN50549-1, C10/C11, AS4777.2, VDE-AR-N4105, VDE0126, IEC62109-1, IEC62109-2, IEC62477-1			
EMC	EN61000-6-2, EN61000-6-3			

Single Phase Hybrid Storage Inverter

4-6 kW Plus Series



The Afore AF low voltage series storage Inverters are designed to increase energy independence for homeowners. The power range is from 4kW to 6kW, compatible with low voltage (40-60V) batteries.

Energy management is based on time-of-use and demand charge rate structures, which significantly reduce the amount of energy purchased from the public grid.

Thanks for the UPS function (switch time < 10ms), that enables the crucial loads power on during outages. Additionally, under the backup operation mode, the inverter provides you up to 150% peak output overloading.

The Afore energy storage inverter features Smart Electricity Pricing & Automation, an energy management tool based on real-time electricity pricing strategies. It continuously monitors electricity price fluctuations and dynamically adjusts device operation accordingly. Operating 24/7 fully automatically without the need for manual intervention, it helps users optimize their electricity usage and reduce energy costs.



AI EMS
Electricity Pricing
& Automation



MAX. 120A
Max. Charge/
Discharge Current 120A



Max. 1.5
PV OVERSIZE
1.5 Times PV Oversize



2 MPPT
MPPT CHANNELS
Up to 2 MPPT Channels



<10 ms
UPS FUNCTION
Switch Time < 10ms



PARALLEL
Max.6 Parallel Stacking



Support for Time-of-use Optimization



Configurable Operation Modes



AFCI (Optional) & Rapid Shutdown Ready



The charging and discharging power of the battery is greater



Build in Anti-feed-in Function



Compact Size and Easy Installation



Smart Monitoring & Remote Firmware Upgrade



Off-grid mode, with a larger load capacity,
the maximum load can be 6KVA

Technical Data	AF4K-SLP	AF4.6K-SLP	AF5K-SLP	AF5.5K-SLP	AF6K-SLP
PV Input					
Max. Input Power (kW)	6	6.9	7.5	8.3	9
Max. PV Voltage (V)	550				
MPPT Range (V)	80 - 500				
Full MPPT Range (V)	120 - 500	130 - 500	150 - 500	160 - 500	170 - 500
Normal Voltage (V)	360				
Startup Voltage (V)	100				
Max. Input Current (A)	18.5 x 2				
Max. Short Current (A)	26 x 2				
No. of MPP Tracker / No. of PV String	2 / 2				
Battery Port					
Max. Charge/Discharge Power (kW)	4.0	4.6	5.0	5.5	6.0
Max. Charge/Discharge Current (A)	120				
Battery Normal Voltage (V)	51.2				
Battery Voltage Range (V)	40 - 60				
Battery Type	Li-ion / Lead-acid etc.				
AC Grid					
Max Continuous Current (A)	19.0	22.0	23.0	26.0	28.0
Max Continuous Power (kVA)	4.0	4.6	5.0	5.5	6.0
Nominal Grid Current (A)	18.2 / 17.4	21.0 / 20.0	22.8 / 21.8	25.0 / 24.0	27.3 / 26.1
Nominal Grid Voltage (V)	198 to 242 @ 220 / 207 to 253 @ 230				
Nominal Grid Frequency (Hz)	50 / 60				
Power Factor	1 default (adjustable from 0.8 leading to 0.8 lagging)				
Current THD (%)	< 3				
AC Load Output					
Max Continuous Current (A)	19.0	22.0	23.0	26.0	28.0
Max Continuous Power (kVA)	4.0	4.6	5.0	5.5	6.0
Max Peak Current (A) (10min)	27.3 / 26.1	31.4 / 30	34.1 / 32.7	37.8 / 36.1	41.0 / 39.2
Max Peak Power (kVA) (10min)	6.0	6.9	7.5	8.3	9.0
Nominal AC Voltage L-N (V)	220 / 230				
Nominal AC Frequency (Hz)	50 / 60				
Switching Time (ms)	Seamless				
Voltage THD (%)	< 3				
Efficiency					
CEC Efficiency (%)	97.0				
Max. Efficiency (%)	97.6				
PV to Bat. Efficiency (%)	98.1				
Bat. between AC Efficiency (%)	96.8				
Protection					
PV Reverse Polarity Protection	Yes				
Over Current/Voltage Protection	Yes				
Anti-Islanding Protection	Yes				
AC Short Circuit Protection	Yes				
Residual Current Detection	Yes				
Ground Fault Monitoring	Yes				
Insulation Resister Detection	Yes				
PV Arc Detection	Yes				
Enclosure Protect Level	IP65 / NEMA4X				
AC/DC surge protection	Type II				
General Data					
Dimensions (W x H x D, mm)	370 x 535 x 192				
Weight (kg)	20.5				
Topology	Transformerless				
Cooling	Intelligent Fan				
Relative Humidity	0 - 100 %				
Operating Temperature Range (°C)	- 25 to 60				
Operating Altitude (m)	< 4000				
Standby Consumption (W)	< 10				
Mounting	Wall Bracket				
Communication with RSD	SUNSPEC				
Display & Communication Interfaces	LCD, LED, RS485, CAN, Wi-Fi, GPRS, 4G, Sunspec				
Certification & Approvals	NRS097, G99, EN50549-1, C10/C11, AS4777.2, VDE-AR-N4105, VDE0126, IEC62109-1, IEC62109-2, IEC62477-1				
EMC	EN61000-6-2, EN61000-6-3				

Off-Grid Inverter

Single Phase / 6 kW



The Afore AF low voltage series storage Inverters are designed to increase energy independence for homeowners. The power is 6 kW and is compatible with low-voltage (40-60 V) batteries.

Energy management is based on time-of-use and demand charge rate structures, which significantly reduce the amount of energy purchased from the public grid.

The Afore energy storage inverter features Smart Electricity Pricing & Automation, an energy management tool based on real-time electricity pricing strategies. It continuously monitors electricity price fluctuations and dynamically adjusts device operation accordingly. Operating 24/7 fully automatically without the need for manual intervention, it helps users optimize their electricity usage and reduce energy costs.



AI EMS
Electricity Pricing
& Automation



MAX. 120A
Max. Charge/
Discharge Current 120A



PV OVERSIZE
2 Times PV Oversize



MPPT CHANNELS
Up to 2 MPPT Channels



BATTERY
Support
Li-ion / Lead-acid

■ Technical Data	AF6K-1L
PV Input	
Max. Input Power (kW)	12
Max. PV Voltage (V)	550
MPPT Range (V)	80 - 500
Full MPPT Range (V)	170 - 500
Normal Voltage (V)	360
Startup Voltage (V)	100
Max. Input Current (A)	18.5 x 2
Max. Short Current (A)	26 x 2
No. of MPP Tracker / No. of PV String	2 / 2
Battery Port	
Max. Charge/Discharge Power (kW)	6
Max. Charge/Discharge Current (A)	120
Battery Normal Voltage (V)	51.2
Battery Voltage Range (V)	40 - 60
Battery Type	Li-ion / Lead-acid etc.
AC Charge (Grid and Generator)	
Max. Continuous Current (A)	28
Max. Continuous Power (kVA)	6
Nominal Grid Current (A)	26.1
Nominal Grid Voltage (V)	L/N/PE, 220Vac, 230Vac
Nominal Grid Frequency (Hz)	50 / 60
Power Factor	1
AC Output	
Nominal Current (A)	26.1
Max. Continuous Current (A)	28
Max. Continuous Power (kVA)	6
Max. Continuous Apparent Power (kVA)	6
Nominal AC Voltage (V)	L/N/PE, 220Vac, 230Vac
Nominal AC Frequency (Hz)	50 / 60
Power Factor	1
Output Voltage Waveform	Pure Sine Wave
Overload Capacity	1.5 times / 10S
THDV	3%
Max Parallel Nr.	6
Efficiency	
CEC Efficiency (%)	97.0
Max. Efficiency (%)	97.6
PV to Bat. Efficiency (%)	98.1
Bat. between AC Efficiency (%)	96.8
Protection	
PV Reverse Polarity Protection	Yes
Over Current/Voltage Protection	Yes
AC Short Circuit Protection	Yes
Residual Current Detection	Yes
Ground Fault Monitoring	Yes
Insulation Resister Detection	Yes
PV Arc Detection	Yes
Ingress protection (IP)	IP66
Protective Class	Class I
Inverter Isolation	Non-isolated (PV - AC - BAT)
Overvoltage Category	OVC III (AC Main), OVC II (DC)
Surge protection	Surge III
General Data	
Dimensions (W x H x D, mm)	370 x 535 x 192
Weight (kg)	20.5
Topology	Transformerless
Cooling	Intelligent Fan
Relative Humidity	0 - 100 %
Operating Temperature Range (°C)	- 25 to 60 (Derating 45)
Operating Altitude (m)	< 4000
Standby Consumption (W)	< 10
Mounting	Wall Bracket
Communication with RSD	SUNSPEC
Display & Communication Interfaces	LCD, LED, RS485, CAN, Wi-Fi, GPRS, 4G, Sunspec

Single Phase Hybrid Storage Inverter

7-12 kW



The Afore AF low voltage series storage Inverters are designed to increase energy independence for homeowners. The power range is from 7kW to 12kW, compatible with low voltage (40-60V) batteries.

Energy management is based on time-of-use and demand charge rate structures, which significantly reduce the amount of energy purchased from the public grid.

Thanks for the UPS function (switch time < 10ms), that enables the crucial loads power on during outages. Additionally, under the backup operation mode, the inverter provides you up to 150% peak output overloading.

The Afore energy storage inverter features Smart Electricity Pricing & Automation, an energy management tool based on real-time electricity pricing strategies. It continuously monitors electricity price fluctuations and dynamically adjusts device operation accordingly. Operating 24/7 fully automatically without the need for manual intervention, it helps users optimize their electricity usage and reduce energy costs.



AI EMS
Electricity Pricing
& Automation



MAX. 370A
Max. Charge/
Discharge Current 370A



Max. 1.5
1.5 Times PV Oversize



2 MPPT
Up to 2 MPPT Channels



<10 ms
Switch Time < 10ms



PARALLEL
Max.6 Parallel Stacking



INPUT
Support Generator

Higher Yields 

Support for Time-of-use Optimization 

Configurable Operation Modes 

AFCI (Optional) & Rapid Shutdown Ready 

Build in Anti-feed-in Function 

Compact Size and Easy Installation 

Smart Monitoring & Remote Firmware Upgrade 

Technical Data	AF7K-SL	AF8K-SL	AF9K-SL	AF10K-SL	AF11K-SL	AF12K-SL
PV Input						
Max. Input Power (kW)	10.5	12	13.5	15	16.5	18
Max. PV Voltage (V)	950					
MPPT Range (V)	80 - 900					
Full MPPT Range (V)	180 - 850	200 - 850	225 - 850	250 - 850	275 - 850	300 - 850
Normal Voltage (V)	650					
Startup Voltage (V)	100					
Max. Input Current (A)	26 + 18.5					
Max. Short Current (A)	32 + 25					
No. of MPP Tracker / No. of PV String	2 / 2					
Battery Port						
Max. Charge/Discharge Power (kW)	10.5	12	13.5	15	16.5	18
Max. Charge/Discharge Current (A)	220	250	280	310	340	370
Normal Charge/Discharge Current(A)	180	200	230	250	275	300
Battery Normal Voltage (V)	51.2					
Battery Voltage Range (V)	40 - 60					
Battery Type	Li-ion / Lead-acid etc.					
AC Grid						
Max Continuous Current (A)	32	37	41	46	50	55
Max Continuous Power (kVA)	7	8	9	10	11	12
Nominal Grid Current (A)	32 / 31	37 / 35	41 / 39	46 / 44	50 / 48	55 / 52
Nominal Grid Voltage (V)	220 / 230					
Nominal Grid Frequency (Hz)	50 / 60					
Power Factor	1 default (adjustable from 0.8 leading to 0.8 lagging)					
Current THD (%)	< 3					
AC Load Output						
Max Continuous Current (A)	32	37	41	46	50	55
Max Continuous Power (kVA)	7	8	9	10	11	12
Max Peak Current (A) (60s)	48 / 46	55.5 / 52.5	61.5 / 58.5	68 / 66	75 / 72	82 / 78
Max Peak Power (kVA) (60s)	10.5	12	13.5	15	16.5	18
Nominal AC Voltage L-N (V)	220 / 230					
Nominal AC Frequency (Hz)	50 / 60					
Switching Time (ms)	Seamless					
Voltage THD (%)	< 3					
Efficiency						
CEC Efficiency (%)	96.8					
Max. Efficiency (%)	98.1					
Protection						
PV Reverse Polarity Protection	Yes					
Bat. Reverse Polarity Protection	Yes					
Over Current/Voltage Protection	Yes					
Anti-Islanding Protection	Yes					
AC Short Circuit Protection	Yes					
Residual Current Detection	Yes					
Ground Fault Monitoring	Yes					
PV Arc Detection	Yes					
Enclosure Protect Level	IP66					
AC/DC surge protection	Type II					
General Data						
Dimensions (W x H x D, mm)	600 x 400 x 250					
Weight (kg)	30					
Topology	Transformerless					
Cooling	Intelligent Fan					
Relative Humidity	0 - 100 %					
Operating Temperature Range (°C)	-25 - 60					
Operating Altitude (m)	< 3000					
Standby Consumption (W)	< 10					
Mounting	Wall Bracket					
Communication with RSD	SUNSPEC					
Display & Communication Interfaces	LCD, LED, RS485, CAN, Wi-Fi, GPRS, 4G, Sunspec					

Single Phase Hybrid Storage Inverter

8-12 kW



The Afore AF low voltage series storage Inverters are designed to increase energy independence for homeowners. The power range is from 8kW to 12kW, compatible with low voltage (40-60V) batteries.

Energy management is based on time-of-use and demand charge rate structures, which significantly reduce the amount of energy purchased from the public grid.

Thanks for the UPS function (switch time < 10ms), that enables the crucial loads power on during outages. Additionally, under the backup operation mode, the inverter provides you up to 150% peak output overloading.

The Afore energy storage inverter features Smart Electricity Pricing & Automation, an energy management tool based on real-time electricity pricing strategies. It continuously monitors electricity price fluctuations and dynamically adjusts device operation accordingly. Operating 24/7 fully automatically without the need for manual intervention, it helps users optimize their electricity usage and reduce energy costs.



AI EMS
Electricity Pricing & Automation



MAX. 240A
Max. Charge/Discharge Current 240A

Max.
1.5

PV OVERSIZE

1.5 Times PV Oversize



3
MPPT

MPPT CHANNELS

Up to 3 MPPT Channels



<10
ms

UPS FUNCTION

Switch Time < 10ms



PARALLEL

Max.6 Parallel Stacking





INPUT
Support Generator









Higher Yields

Support for Time-of-use Optimization

Configurable Operation Modes

AFCI (Optional) & Rapid Shutdown Ready

Colorful touch LCD, User-friendly

Build in Anti-feed-in Function

Compact Size and Easy Installation

Smart Monitoring & Remote Firmware Upgrade

■ Technical Data	AF8K-SLP	AF9K-SLP	AF10K-SLP	AF11K-SLP	AF12K-SLP
PV Input					
Max. Input Power (kW)	12	13.5	15	16.5	18
Max. PV Voltage (V)	550				
MPPT Range (V)	80 - 500				
Full MPPT Range (V)	150 - 500	170 - 500	190 - 500	210 - 500	230 - 500
Normal Voltage (V)	360				
Startup Voltage (V)	100				
Max. Input Current (A)	18.5 x 3				
Max. Short Current (A)	26 x 3				
No. of MPP Tracker / No. of PV String	3 / 1+1+2				
Battery Port					
Max. Charge/Discharge Power (kW)	8.0	9.0	10	11	12
Max. Charge/Discharge Current (A)	200	240	240	240	240
Battery Normal Voltage (V)	51.2				
Battery Voltage Range (V)	40 - 60				
Battery Type	Li-ion / Lead-acid etc.				
AC Grid & Diesel Gen (Optional)					
Max Continuous Current (A)	37	41	46	50	55
Max Continuous Power (kVA)	8.0	9.0	10	11	12
Nominal Grid Current (A)	36.4 / 34.8	41 / 39.2	45.5 / 43.5	50 / 47.9	54.6 / 52.2
Nominal Grid Voltage (V)	198 to 242 @ 220 / 207 to 253 @ 230				
Nominal Grid Frequency (Hz)	50 / 60				
Power Factor	1 default (adjustable from 0.8 leading to 0.8 lagging)				
Current THD (%)	< 3				
AC Load Output					
Max Continuous Current (A)	37	41	46	50	55
Max Continuous Power (kVA)	8	9	10	11	12
Max Peak Current (A) (10min)	55.5	61.5	69	75	82.5
Max Peak Power (kVA) (10min)	12	13.5	15	16.5	18
Nominal AC Voltage L-N (V)	220 / 230				
Nominal AC Frequency (Hz)	50 / 60				
Switching Time (ms)	Seamless				
Voltage THD (%)	< 3				
Efficiency					
European Efficiency (%)	96.8				
Max. Efficiency (%)	98.1				
Protection					
PV Reverse Polarity Protection	Yes				
Bat. Reverse Polarity Protection	Yes				
Over Current/Voltage Protection	Yes				
Anti-Islanding Protection	Yes				
AC Short Circuit Protection	Yes				
Residual Current Detection	Yes				
Ground Fault Monitoring	Yes				
PV Arc Detection	Yes				
Enclosure Protect Level	IP66				
General Data					
Dimensions (W x H x D, mm)	785 x 614 x 258				
Weight (kg)	51				
Topology	Transformerless				
Cooling	Intelligent Fan				
Relative Humidity	0 - 100 %				
Operating Temperature Range (°C)	- 25 to 60 (Derating 45)				
Operating Altitude (m)	< 4000				
Standby Consumption (W)	< 30				
Mounting	Wall Bracket				
Communication with RSD	SUNSPEC				
Display & Communication Interfaces	LCD, LED, RS485, CAN, Wi-Fi, GPRS, 4G, Sunspec				
Certification & Approvals	CE, IEC62116, IEC61727, IEC61683, IEC60068				
EMC	EN61000-6-2, EN61000-6-3				

| Wall-mounted Residential ESS



Wall-mounted or
floor-standing



Safe LFP cells and
smart BMS



Scalable up to 30kWh

Model		AF5000W-LP
Parameter		
Total Energy		5.22kWh
Usable Energy		4.96kWh
Voltage		44.8~57.6Vdc
Nominal Voltage		51.2Vd.c.
Rated Capacity		102Ah
Max.Charge Voltage		57.6Vd.c.
Nominal Discharging Current		60A
Nominal Charging Current		60A
Weight		47kg
Dimension(mm)(H*L*W)		680*480*180mm
Max.recommended DOD		95%
Operating Condition		Indoor or outdoor
Operating	Charging	0~50°C
Temperature	Discharging	-15~50°C
Storage Temperature Range		> 1 month 0~35°C / ≤1 month -20~45°C
Humidity		15% ~ 85%RH (No Condensation)
Over Voltage Category		II
Cooling Type		Natural cooling
Case Material		Metal
Installation		Wall-mounted or floor-standing
IP Rating		IP 66
Protective Class		I
Max.Connection Number		6P
Communication		CAN/ RS485
Battery Protection		Over-current/Over-voltage/Short circuit/ Under-voltage/Over temperature
Certificates		CE,IEC62619,IEC61000,IEC62040,IEC63056,UN38.3,MSDS

*Testing conditions based on temperature 25°C at the beginning of life. Total Energy/Usable Energy are measured with a standard test method: 0.2C Charge and Discharge. As per the characteristics of lithium batteries, such parameters as the charge/ discharge current and efficiency listed above are subject to change.

| Wall-mounted Residential ESS



Large Capacity



Built-in BMS Protection



Reliable Backup Power



Reliable Operation



Optimal Management

■ Model

AF10000W-LA0

Parameter	
Total Energy	10.49kWh
Usable Energy	9.97kWh
Voltage	44.8~57.6Vdc
Nominal Voltage	51.2Vd.c.
Rated Capacity	57.6Vd.c.
Max.Charge Voltage	205Ah
Nominal Discharging Current	100A(1P) /160A(2P~6P)
Nominal Charging Current	100A(1P) /160A(2P~6P)
Weight	87kg
Dimension(mm)(H*L*W)	670*430*230mm
Max.recommended DOD	95%
Operating Condition	Indoor or outdoor
Operating Charging	0~55°C
Temperature Discharging	-15~55°C
Standard Ambient Temperature Range	0~40°C
Storage Temperature Range	>1 month 0~35°C / ≤1 month -20~45°C
Humidity	15% ~ 85%RH (No Condensation)
Over Voltage Category	II
Cooling Type	Natural cooling
Case Material	Metal
Installation	floor-standing
IP Rating	IP 66
Heating unit(optional)	130W
Protective Class	I
Max. Connection Number	6P
Communication	CAN / RS485 / Wifi
Battery Protection	Over-current/Over-voltage/Short circuit/ Under-voltage/Over-temperature
Certificates	CE,UN38.3,MSDS

*Testing conditions based on temperature 25°C at the beginning of life. Total Energy/Usable Energy are measured with a standard test method: 0.2C Charge and Discharge. As per the characteristics of lithium batteries, such parameters as the charge/ discharge current and efficiency listed above are subject to change.

Movable Residential ESS



Large Capacity



Built-in BMS Protection



Reliable Backup Power



High Quality 360° Wheels



Reliable Operation



Optimal Management

Model		AF16000W-LZ
Parameter		
Total Energy		16.07kWh
Usable Energy		15.27kWh
Voltage		44.8~57.6Vd.c.
Nominal Voltage		51.2Vd.c.
Rated Capacity		314Ah
Max.Charge Voltage		57.6Vd.c.
Nominal Discharging Current		150A(1P) /160A(2P~6P)
Nominal Charging Current		150A(1P) /160A(2P~6P)
Weight		120kg
Dimension(mm)(H*L*W)		800*680*230mm
Max.recommended DOD		95%
Operating Condition		Indoor or outdoor
Operating	Charging	0~55°C
Temperature	Discharging	-15~55°C
Standard Ambient Temperature Range		0~40°C
Storage Temperature Range		0°C to 40°C @60+25% Relative Humidity
Humidity		15% ~ 85%RH (No Condensation)
Over Voltage Category		II
Cooling Type		Natural cooling
Case Material		Metal
Installation		Floor-standing
IP Rating		IP 66
Heating unit(optional)		150W
Protective Class		I
Max. Connection Number		6P
Communication		CAN / RS485
WiFi		Yes
Battery Protection		Over-current/Over-voltage/Short circuit/ Under-voltage/Over-temperature
Certificates		CE,UN38.3,MSDS

*Testing conditions based on temperature 25°C at the beginning of life. Total Energy/Usable Energy are measured with a standard test method: 0.2C Charge and Discharge. As per the characteristics of lithium batteries, such parameters as the charge/ discharge current and efficiency listed above are subject to change.

Three Phase Hybrid Storage Inverter

7-12 kW (LV Battery Supported)



The Afore AF low voltage series storage Inverters are designed to increase energy independence for homeowners. The power range is from 7kW to 12kW, compatible with low voltage (40-60V) batteries.

Energy management is based on time-of-use and demand charge rate structures, which significantly reduce the amount of energy purchased from the public grid.

Thanks for the UPS function (switch time < 10ms), that enables the crucial loads power on during outages. Additionally, under the backup operation mode, the inverter provides you up to 150% peak output overloading.

The Afore energy storage inverter features Smart Electricity Pricing & Automation, an energy management tool based on real-time electricity pricing strategies. It continuously monitors electricity price fluctuations and dynamically adjusts device operation accordingly. Operating 24/7 fully automatically without the need for manual intervention, it helps users optimize their electricity usage and reduce energy costs.



AI EMS
Electricity Pricing & Automation



MAX. 370A
Max. Charge/Discharge Current 370A



100% UNBALANCE
Support Unbalance Load



2 MPPT
Up to 2 MPPT Channels



10 ms
Switch Time < 10ms



PARALLEL
Max.6 Parallel Stacking



INPUT
Support Generator

- Higher Yields

Support for Time-of-use Optimization

Configurable Operation Modes

AFCI (Optional) & Rapid Shutdown Ready
-  48V low voltage battery, transformer isolation design

 Build in Anti-feed-in Function

 Compact Size and Easy Installation

 Smart Monitoring & Remote Firmware Upgrade

Technical Data	AF7K-TL	AF8K-TL	AF9K-TL	AF10K-TL	AF11K-TL	AF12K-TL
PV Input						
Max. Input Power (kW)	10.5	12	13.5	15	16.5	18
Max. PV Voltage (V)	950					
MPPT Range (V)	80 - 900					
Full MPPT Range (V)	180 - 850	200 - 850	225 - 850	250 - 850	275 - 850	300 - 850
Normal Voltage (V)	650					
Startup Voltage (V)	100					
Max. Input Current (A)	26 + 18.5					
Max. Short Current (A)	32 + 25					
No. of MPP Tracker / No. of PV String	2 / 2					
Battery Port						
Max. Charge/Discharge Power (kW)	10.5	12	13.5	15	16.5	18
Max. Charge/Discharge Current (A)	220	250	280	310	340	370
Normal Charge/Discharge Current(A)	180	200	230	250	275	300
Battery Normal Voltage (V)	51.2					
Battery Voltage Range (V)	40 - 60					
Battery Type	Li-ion / Lead-acid etc.					
AC Grid						
Max Continuous Current (A)	11	12	14	15	17	18
Max Continuous Power (kVA)	7	8	9	10	11	12
Nominal Grid Current (A)	11 / 10.5	12 / 11.5	14 / 13	15 / 14.5	17 / 16	18 / 17.5
Nominal Grid Voltage (V)	380 / 400					
Nominal Grid Frequency (Hz)	50 / 60					
Power Factor	1 default (adjustable from 0.8 leading to 0.8 lagging)					
Current THD (%)	< 3					
AC Load Output						
Max Continuous Current (A)	11	12	14	15	17	18
Max Continuous Power (kVA)	7	8	9	10	11	12
Max Peak Current (A) (60s)	22 / 21	24 / 23	28 / 26	30 / 29	34 / 32	36 / 35
Max Peak Power (kVA) (60s)	10.5	12	13.5	15	16.5	18
Nominal AC Voltage L-N (V)	380 / 400					
Nominal AC Frequency (Hz)	50 / 60					
Switching Time (ms)	Seamless					
Voltage THD (%)	< 3					
Efficiency						
CEC Efficiency (%)	96.8					
Max. Efficiency (%)	98.1					
Protection						
PV Reverse Polarity Protection	Yes					
Bat. Reverse Polarity Protection	Yes					
Over Current/Voltage Protection	Yes					
Anti-Islanding Protection	Yes					
AC Short Circuit Protection	Yes					
Residual Current Detection	Yes					
Ground Fault Monitoring	Yes					
PV Arc Detection	Yes					
Enclosure Protect Level	IP66					
AC/DC surge protection	Type II					
General Data						
Dimensions (W x H x D, mm)	600 x 400 x 250					
Weight (kg)	30					
Topology	Transformerless					
Cooling	Intelligent Fan					
Relative Humidity	0 - 100 %					
Operating Temperature Range (°C)	-25 - 60					
Operating Altitude (m)	< 3000					
Standby Consumption (W)	< 10					
Mounting	Wall Bracket					
Communication with RSD	SUNSPEC					
Display & Communication Interfaces	LCD, LED, RS485, CAN, Wi-Fi, GPRS, 4G, Sunspec					

Three Phase Hybrid Storage Inverter

3-15 kW



The Afore AF series three phase storage inverters are designed to increase energy independence for homeowners and commercial users. The power range is from 3.0kW to 15kW, compatible with high voltage (80-600V) batteries.


Energy management is based on time-of-use and demand charge rate structures, significantly reduce the amount of energy purchased from public grid.

Thanks for the UPS function (switch time < 10ms), that enables the crucial loads power on during outages. Additionally, under the backup operation mode, the inverter provides you up to 150% peak output overloading.



The Afore energy storage inverter features Smart Electricity Pricing & Automation, an energy management tool based on real-time electricity pricing strategies. It continuously monitors electricity price fluctuations and dynamically adjusts device operation accordingly. Operating 24/7 fully automatically without the need for manual intervention, it helps users optimize their electricity usage and reduce energy costs.

						
AI EMS Electricity Pricing & Automation	WIDE RANGE Voltage Range (80-600V)	Max. 1.5 1.5 Times PV Oversize	Max. 18.5A String Current Up To 18.5A	<10 ms Switch Time < 10ms	COMPACT Compact Design	GENERATOR Generator Backup Support
Support for Time-of-use Optimization 		Build in Anti-feed-in Function 		Configurable Operation Modes 		
AFCI (Optional) & Rapid Shutdown Ready 		100% unbalanced output, each phase 		Smart Monitoring & Remote Firmware Upgrade 		

For New Storage System:




Optimizing Self-Consumption (on-grid) + Emergency Power Supply(off-grid)



Optimizing Self-Consumption Mode

With home energy storage installed, home owners may also be able to change from a flat rate electricity tariff to a time-of-use tariff. For the areas and regions, where peak shaving can be applied.



■ Technical Data	AF3K-MTH	AF4K-MTH	AF5K-MTH	AF6K-MTH
PV Input				
Max. DC Input Power (kW)	5	6	7.5	9
Max. PV Voltage (V)		1000		
Rated DC Input Voltage (V)		620		
DC Input Voltage Range (V)		150 - 1000		
MPPT Voltage Range (V)		150 - 850		
Full MPPT Range(V)		200 - 850		250 - 850
Start-up Voltage (V)		160		
Max. DC Input Current (A)		18.5 x 2		
Max. Short Current(A)		25 x 2		
No. of MPPT Tracker / Strings		2/2		
Battery Port				
Battery Nominal Voltage (V)	350	350	350	350
Battery Voltage Range (V)		80 - 600		
Max. Charge/Discharge Current (A)		30		
Max. Charge/Discharge Power (kW)	3	4	5	6
Charging Curve		3 Stages		
Compatible Battery Type		Li-ion / Lead-acid / Sodium metal chloride battery		
AC Grid				
Nominal AC Output Power (kW)	3	4	5	6
Max. AC Input/Output Power (kVA)	4.5 / 3.3	6 / 4.4	7.5 / 5.5	9 / 6.6
Max. AC Output Current (A)	5.3	7	8.5	10.5
Nominal AC Voltage (V)		3P+N+PE/3P+PE 230/400		
Nominal AC Frenquency (Hz)		50/60		
Power Factor		1 (-0.8-0.8 adjustable)		
Current THD (%)		<3%		
AC Load Output (Back-up)				
Nominal Output Power (kVA)	3	4	5	6
Nominal Output Voltage (V)		3P+N+PE/3P+PE 230/400		
Nominal Output Frequency (Hz)		50/60		
Nominal Output Current (A)	4.4	5.8	7.3	8.7
Peak Output Power	3.3kVA, 60s	4.4kVA, 60s	5.5kVA, 60s	6.6kVA, 60s
THDV (with linear load)		<3%		
Switching Time (ms)		<10		
Efficiency				
Europe Efficiency		97.50%		
Max. Efficiency		98.00%		
Battery Charge/Discharge Efficiency		98.00%		
Protection				
Reverse Polarity Protection		Yes		
Over Current / Voltage Protection		Yes		
Anti-islanding Protection		Yes		
AC Short-circuit Protection		Yes		
Leakage Current Detection		Yes		
Ground Fault Monitoring		Yes		
Grid Monitoring		Yes		
Enclosure Protect Level		IP66		
AC/DC surge protection		Type II		
General Data				
Dimensions (W x H x D, mm)		370 x 598.5 x 192mm		
Weight (kg)		22kg		
Topology		Transformerless		
Cooling Concept		Natural Convection		
Relatively Humidity		0 - 100%		
Operating Temperature Range (°C)		- 25 to 60 °C		
Operating Altitude (m)		<4000		
Standby Consumption (W)		<5		
Display & Communication Interfaces		LCD, LED, RS485, CAN, Wi-Fi, GPRS, 4G, Sunspec		
Certification & Approvals	NRS097, G98/G99, EN50549-1, C10/C11, AS4777.2, VDE-AR-N4105, VDE0126, IEC62109-1, IEC62109-2, IEC62477-1			
EMC		EN61000-6-2, EN61000-6-3		

■ Technical Data	AF8K-MTH	AF10K-MTH	AF12K-MTH	AF15K-MTH
PV Input				
Max. DC Input Power (kW)	12	15	18	22.5
Max. PV Voltage (V)		1000		
Rated DC Input Voltage (V)		620		
DC Input Voltage Range (V)		150 - 1000		
MPPT Voltage Range (V)		150 - 850		
Full MPPT Range(V)	300 - 850		500 - 850	
Start-up Voltage (V)		160		
Max. DC Input Current (A)		18.5 x 2		
Max. Short Current(A)		25 x 2		
No. of MPPT Tracker / Strings		2/2		
Battery Port				
Battery Nominal Voltage (V)	350	350	450	500
Battery Voltage Range (V)		80 - 600		
Max. Charge/Discharge Current (A)		30		
Max. Charge/Discharge Power (kW)	8	10	12	15
Charging Curve		3 Stages		
Compatible Battery Type		Li-ion / Lead-acid / Sodium metal chloride battery		
AC Grid				
Nominal AC Output Power (kW)	8	10	12	15
Max. AC Input/Output Power (kVA)	12 / 8.8	15 / 11	18 / 13.2	22.5 / 16.5
Max. AC Output Current (A)	13.5	17	21.5	27
Nominal AC Voltage (V)		3P+N+PE/3P+PE 230/400		
Nominal AC Frenquency (Hz)		50/60		
Power Factor		1 (-0.8-0.8 adjustable)		
Current THD (%)		<3%		
AC Load Output (Back-up)				
Nominal Output Power (kVA)	8	10	12	15
Nominal Output Voltage (V)		3P+N+PE/3P+PE 230/400		
Nominal Output Frequency (Hz)		50/60		
Nominal Output Current (A)	11.6	14.5	17.4	21.8
Peak Output Power	8.8kVA, 60s	11kVA, 60s	13.2kVA, 60s	16.5kVA, 60s
THDV (with linear load)		<3%		
Switching Time (ms)		<10		
Efficiency				
Europe Efficiency		97.50%		
Max. Efficiency	98.20%		98.30%	
Battery Charge/Discharge Efficiency		98.00%		
Protection				
Reverse Polarity Protection		Yes		
Over Current / Voltage Protection		Yes		
Anti-islanding Protection		Yes		
AC Short-circuit Protection		Yes		
Leakage Current Detection		Yes		
Ground Fault Monitoring		Yes		
Grid Monitoring		Yes		
Enclosure Protect Level		IP66		
AC/DC surge protection		Type II		
General Data				
Dimensions (W x H x D, mm)		370 x 598.5 x 192mm		
Weight (kg)		22kg		
Topology		Transformerless		
Cooling Concept		Intelligent Fan		
Relatively Humidity		0 - 100%		
Operating Temperature Range (°C)		- 25 to 60 °C		
Operating Altitude (m)		<4000		
Standby Consumption (W)		<5		
Display & Communication Interfaces		LCD, LED, RS485, CAN, Wi-Fi, GPRS, 4G, Sunspec		
Certification & Approvals	NRS097, G98/G99, EN50549-1, C10/C11, AS4777.2, VDE-AR-N4105, VDE0126, IEC62109-1, IEC62109-2, IEC62477-1			
EMC		EN61000-6-2, EN61000-6-3		

Three Phase Hybrid Storage Inverter

3-30 kW



The Afore AF series three phase storage inverters are designed to increase energy independence for homeowners and commercial users. The power range is from 3.0kW to 30kW, compatible with high voltage (150-800V) batteries.

Energy management is based on time-of-use and demand charge rate structures, significantly reduce the amount of energy purchased from public grid.

Thanks for the UPS function (switch time < 10ms), that enables the crucial loads power on during outages. Additionally, under the backup operation mode, the inverter provides you up to 150% peak output overloading.

The Afore energy storage inverter features Smart Electricity Pricing & Automation, an energy management tool based on real-time electricity pricing strategies. It continuously monitors electricity price fluctuations and dynamically adjusts device operation accordingly. Operating 24/7 fully automatically without the need for manual intervention, it helps users optimize their electricity usage and reduce energy costs.

AI EMS
Electricity Pricing & Automation

BATTERY
Support Sodium metal chloride battery

WIDE RANGE
Voltage Range (150-800V)

100% UNBALANCE
Support Unbalance Load

Max. 40A
String Current Up To 40A

UPS FUNCTION
Switch Time < 10ms

INPUT
Support Generator

Support for Time-of-use Optimization

Configurable Operation Modes


AFCI (Optional) & Rapid Shutdown Ready

Build in Anti-feed-in Function


100% unbalanced output, each phase;
200% unbalanced output, each phase (≤ 10kW)

Smart Monitoring & Remote Firmware Upgrade

For New Storage System:




Optimizing Self-Consumption (on-grid) + Emergency Power Supply (off-grid)



Optimizing Self-Consumption Mode

With energy storage system installed, users may also be able to change from a flat rate electricity tariff to a time-of-use tariff. For the areas and regions, where peak shaving can be applied.



Technical Data	AF3K-TH	AF4K-TH	AF5K-TH	AF6K-TH	AF8K-TH	AF10K-TH
PV Input						
Max. DC Input Power (kW)	5	6	7.5	9	12	15
Max. PV Voltage (V)	1000					
Rated DC Input Voltage (V)	620					
DC Input Voltage Range (V)	150-1000					
MPPT Voltage Range (V)	150-850					
Full MPPT Range(V)	200-850			250-850	300-850	500-850
Start-up Voltage (V)	160					
Max. DC Input Current (A)	20x2					
Max. Short Current(A)	30x2					
No. of MPPT Tracker / Strings	2/2					
Battery Port						
Battery Nominal Voltage (V)	200	200	200	250	300	400
Battery Voltage Range (V)	150-800					
Max. Charge/Discharge Current (A)	30					
Max. Charge/Discharge Power (kW)	3	4	5	6	8	10
Charging Curve	3 Stages					
Compatible Battery Type	Li-ion / Lead-acid / Sodium metal chloride battery					
AC Grid						
Nominal AC Output Power (kW)	3	4	5	6	8	10
Max. AC Input/Output Power (kVA)	4.5 / 3.3	6 / 4.4	7.5 / 5.5	9 / 6.6	12 / 8.8	15 / 11
Max. AC Output Current (A)	5.3	7	8.5	10.5	13.5	17
Nominal AC Voltage (V)	230/400					
Nominal AC Frenquency (Hz)	50/60					
Power Factor	1 (-0.8-0.8 adjustable)					
Current THD (%)	<3%					
AC Load Output (Back-up)						
Nominal Output Power (kVA)	3	4	5	6	8	10
Nominal Output Voltage (V)	230/400					
Nominal Output Frequency (Hz)	50/60					
Nominal Output Current (A)	4.4	5.8	7.3	8.7	11.6	14.5
Peak Output Power	3.3kVA, 60s	4.4kVA, 60s	5.5kVA, 60s	6.6kVA, 60s	8.8kVA, 60s	11kVA, 60s
THDV (with linear load)	<3%					
Switching Time (ms)	<10					
Efficiency						
Europe Efficiency	97.50%					
Max. Efficiency	98.00%				98.20%	
Battery Charge/Discharge Efficiency	98.00%					
Protection						
Reverse Polarity Protection	Yes					
Over Current / Voltage Protection	Yes					
Anti-islanding Protection	Yes					
AC Short-circuit Protection	Yes					
Leakage Current Detection	Yes					
Ground Fault Monitoring	Yes					
Grid Monitoring	Yes					
Enclosure Protect Level	IP65					
AC/DC surge protection	Type II					
General Data						
Dimensions (W x H x D, mm)	558 x 535 x 260 mm					
Weight (kg)	29kg					
Topology	Transformerless					
Cooling Concept	Natural Convection				Intelligent Fan	
Relatively Humidity	0-100%					
Operating Temperature Range (°C)	-25 to 60 °C					
Operating Altitude (m)	<4000					
Standby Consumption (W)	<5					
Display & Communication Interfaces	LCD, LED, RS485, CAN, Wi-Fi, GPRS, 4G, Sunspec					
Certification & Approvals	NRS097, G98, EN50549-1, C10/C11, AS4777.2, VDE-AR-N4105, VDE0126, IEC62109-1, IEC62109-2, IEC62477-1					
EMC	EN61000-6-2, EN61000-6-3					

Technical Data	AF12K-TH	AF15K-TH	AF17K-TH	AF20K-TH	AF25K-TH	AF30K-TH
PV Input						
Max. DC Input Power (kW)	18	22.5	25.5	30	37.5	45
Max. PV Voltage (V)	1000					
Rated DC Input Voltage (V)	620					
DC Input Voltage Range (V)	150 - 1000					
MPPT Voltage Range (V)	150 - 850					
Full MPPT Range(V)	500 - 850					
Start-up Voltage (V)	160					
Max. DC Input Current (A)	20x2	20 + 32	32x2	40x2		
Max. Short Current(A)	30x2	30 + 48	48x2	60x2		
No. of MPPT Tracker / Strings	2/2	2/3	2/4	2/4		
Battery Port						
Battery Nominal Voltage (V)	450	500	400	500	500	550
Battery Voltage Range (V)	150 - 800					
Max. Charge/Discharge Current (A)	30	50	50	50	60	60
Max. Charge/Discharge Power (kW)	12	15	17	20	25	30
Charging Curve	3 Stages					
Compatible Battery Type	Li-ion / Lead-acid / Sodium metal chloride battery					
AC Grid						
Nominal AC Output Power (kW)	12	15	17	20	25	30
Max. AC Input/Output Power (kVA)	18 / 13.2	22.5 / 16.5	25.5 / 18.7	30 / 22	37.5 / 27.5	45 / 33
Max. AC Output Current (A)	21.5	27	30	32	40	48
Nominal AC Voltage (V)	230 / 400					
Nominal AC Frenquency (Hz)	50 / 60					
Power Factor	1 (- 0.8 - 0.8 adjustable)					
Current THD (%)	< 3 %					
AC Load Output (Back-up)						
Nominal Output Power (kVA)	12	15	17	20	25	30
Nominal Output Voltage (V)	230 / 400					
Nominal Output Frequency (Hz)	50 / 60					
Nominal Output Current (A)	17.4	21.8	24.7	29	36.3	43.5
Peak Output Power	13.2kVA, 60s	16.5kVA, 60s	18.7kVA, 60s	22kVA, 60s	27.5kVA, 60s	33kVA, 60s
THDV (with linear load)	< 3 %					
Switching Time (ms)	< 10					
Efficiency						
Europe Efficiency	97.50%		97.80%		98.00%	98.10%
Max. Efficiency	98.30%				98.50%	
Battery Charge/Discharge Efficiency	98.00%					
Protection						
Reverse Polarity Protection	Yes					
Over Current / Voltage Protection	Yes					
Anti-islanding Protection	Yes					
AC Short-circuit Protection	Yes					
Leakage Current Detection	Yes					
Ground Fault Monitoring	Yes					
Grid Monitoring	Yes					
Enclosure Protect Level	IP65					
AC/DC surge protection	Type II					
General Data						
Dimensions (W x H x D, mm)	558 x 535 x 260 mm					
Weight (kg)	29kg			36kg		
Topology	Transformerless					
Cooling Concept	Intelligent Fan					
Relatively Humidity	0 - 100 %					
Operating Temperature Range (°C)	- 25 to 60 °C					
Operating Altitude (m)	< 4000					
Standby Consumption (W)	< 5					
Display & Communication Interfaces	LCD, LED, RS485, CAN, Wi-Fi, GPRS, 4G, Sunspec					
Certification & Approvals	NRS097, G99, EN50549-1, C10/C11, AS4777.2, VDE-AR-N4105, VDE0126, IEC62109-1, IEC62109-2, IEC62477-1					
EMC	EN61000-6-2, EN61000-6-3					

Three Phase Hybrid Storage Inverter

3-12 kW Plus Series



The Afore three phase storage inverters plus series are designed to increase energy independence for homeowners and commercial users. The power range is from 3.0kW to 12kW, compatible with high voltage (80-600V and 120-650V) batteries.

Energy management is based on time-of-use and demand charge rate structures, significantly reduce the amount of energy purchased from public grid.

Thanks for the UPS function (switch time < 10ms), that enables the crucial loads power on during outages. Additionally, under the backup operation mode, the inverter provides you up to 150% peak output overloading.

The Afore energy storage inverter features Smart Electricity Pricing & Automation, an energy management tool based on real-time electricity pricing strategies. It continuously monitors electricity price fluctuations and dynamically adjusts device operation accordingly. Operating 24/7 fully automatically without the need for manual intervention, it helps users optimize their electricity usage and reduce energy costs.



AI EMS
Electricity Pricing & Automation



BATTERY
Support
Sodium metal chloride battery



MIN. 80V
Battery Voltage
Minimum 80V



MAX. 50A
Max. Charge/
Discharge Current 50A



100% UNBALANCE
Support Unbalance Load



Max. 20A
String Current Up To 20A



<10 ms
UPS FUNCTION
Switch Time < 10ms

- Support for Time-of-use Optimization

Configurable Operation Modes

AFCI (Optional) & Rapid Shutdown Ready
-  Build in Anti-feed-in Function

 100% unbalanced output, each phase;
200% unbalanced output, each phase (≤ 10kW)

 Smart Monitoring & Remote Firmware Upgrade

Technical Data	AF3K-THP	AF4K-THP	AF5K-THP	AF6K-THP	AF8K-THP	AF10K-THP	AF12K-THP
PV Input							
Max. DC Input Power (kW)	5	6	7.5	9	12	15	18
Max. PV Voltage (V)				1000			
Rated DC Input Voltage (V)				620			
DC Input Voltage Range (V)				150-1000			
MPPT Voltage Range (V)				150-850			
Full MPPT Range(V)	200-850			250-850	300-850	500-850	
Start-up Voltage (V)				160			
Max. DC Input Current (A)				20x2			
Max. Short Current(A)				30x2			
No. of MPPT Tracker / Strings				2/2			
Battery Port							
Battery Nominal Voltage (V)	100	100	100	150	200	250	300
Battery Voltage Range (V)				80-600			120-650
Max. Charge/Discharge Current (A)				50			
Max. Charge/Discharge Power (kW)	3	4	5	6	8	10	12
Charging Curve				3 Stages			
Compatible Battery Type				Li-ion / Lead-acid / Sodium metal chloride battery			
AC Grid							
Nominal AC Output Power (kW)	3	4	5	6	8	10	12
Max. AC Input/Output Power (kVA)	4.5 / 3.3	6 / 4.4	7.5 / 5.5	9 / 6.6	12 / 8.8	15 / 11	18 / 13.2
Max. AC Output Current (A)	5.3	7	8.5	10.5	13.5	17	21.5
Nominal AC Voltage (V)				230/400			
Nominal AC Frenquency (Hz)				50/60			
Power Factor				1 (-0.8-0.8 adjustable)			
Current THD (%)				<3%			
AC Load Output (Back-up)							
Nominal Output Power (kVA)	3	4	5	6	8	10	12
Nominal Output Voltage (V)				230/400			
Nominal Output Frequency (Hz)				50/60			
Nominal Output Current (A)	4.4	5.8	7.3	8.7	11.6	14.5	17.4
Peak Output Power	3.3kVA, 60s	4.4kVA, 60s	5.5kVA, 60s	6.6kVA, 60s	8.8VA, 60s	11VA, 60s	13.2kVA, 60s
THDV (with linear load)				<3%			
Switching Time (ms)				<10			
Efficiency							
Europe Efficiency				97.50%			
Max. Efficiency	98.00%					98.20%	98.30%
Battery Charge/Discharge Efficiency				98.00%			
Protection							
Reverse Polarity Protection				Yes			
Over Current / Voltage Protection				Yes			
Anti-islanding Protection				Yes			
AC Short-ciruit Protection				Yes			
Leakage Current Detection				Yes			
Ground Fault Monitoring				Yes			
Grid Monitoring				Yes			
Enclosure Protect Level				IP65			
AC/DC surge protection				Type II			
General Data							
Dimensions (W x H x D, mm)				558 x 535 x 260 mm			
Weight (kg)				29kg			
Topology				Transformerless			
Cooling Concept	Natural Convection					Intelligent Fan	
Relative Humidity				0-100%			
Operating Temperature Range (°C)				-25 to 60 °C			
Operating Altitude (m)				<4000			
Standby Consumption (W)				<5			
Display & Communication Interfaces				LCD, LED, RS485, CAN, Wi-Fi, GPRS, 4G, Sunspec			
Certification & Approvals	NRS097, G98/G99, EN50549-1, C10/C11, AS4777.2, VDE-AR-N4105, VDE0126, IEC62109-1, IEC62109-2, IEC62477-1						
EMC	EN61000-6-2, EN61000-6-3						

Three Phase Hybrid Storage Inverter

36-60 kW



The Afore AF series three phase storage inverters are designed to increase energy independence for homeowners and commercial users. The power range is from 36kW to 60kW, compatible with high voltage (150-800V) batteries.

Energy management is based on time-of-use and demand charge rate structures, significantly reduce the amount of energy purchased from public grid.

Thanks for the UPS function (switch time < 10ms), that enables the crucial loads power on during outages. Additionally, under the backup operation mode, the inverter provides you up to 150% peak output overloading.

The Afore energy storage inverter features Smart Electricity Pricing & Automation, an energy management tool based on real-time electricity pricing strategies. It continuously monitors electricity price fluctuations and dynamically adjusts device operation accordingly. Operating 24/7 fully automatically without the need for manual intervention, it helps users optimize their electricity usage and reduce energy costs.



AI EMS
Electricity Pricing & Automation



BATTERY
Support Sodium metal chloride battery



WIDE RANGE
Voltage Range (150-800V)



100% UNBALANCE
Support Unbalance Load



Max. 40A
String Current Up To 40A



UPS FUNCTION
Switch Time < 10ms



INPUT
Support Generator



Support 280AH, 315AH battery system



Support for Time-of-use Optimization



Configurable Operation Modes



AFCI (Optional) & Rapid Shutdown Ready



2 times AC Oversize



Build in Anti-feed-in Function



100% unbalanced output, each phase



Smart Monitoring & Remote Firmware Upgrade

Technical Data	AF36K-TH	AF40K-TH	AF45K-TH	AF50K-TH	AF60K-TH
PV Input					
Max. DC Input Power (kW)	54	60	67.5	75	90
Max. PV Voltage (V)			1000		
Rated DC Input Voltage (V)			620		
DC Input Voltage Range (V)			150-1000		
MPPT Voltage Range (V)			150-850		
Full MPPT Range(V)			500-850		
Start-up Voltage (V)			160		
Max. DC Input Current (A)			40×4		
Max. Short Current(A)			48×4		
No. of MPPT Tracker / Strings			4/8		
Battery Port					
Battery Nominal Voltage (V)			500		
Battery Voltage Range (V)			150-800		
Max. Charge/Discharge Current (A)			120		
Max. Charge/Discharge Power (kW)	36	40	45	50	60
Charging Curve			3 Stages		
Compatible Battery Type		Li-ion / Lead-acid / Sodium metal chloride battery			
AC Grid					
Nominal AC Output Power (kW)	36	40	45	50	60
Max. AC Input/Output Power (kVA)	54 / 39.6	60 / 44	67.5 / 49.5	75 / 55	90 / 66
Max. AC Output Current (A)	60.5	67	75.5	83.5	96
Nominal AC Voltage (V)			230/400		
Nominal AC Frenquency (Hz)			50/60		
Power Factor		1 (-0.8-0.8 adjustable)			
Current THD (%)			<3%		
AC Load Output (Back-up)					
Nominal Output Power (kVA)	36	40	45	50	60
Nominal Output Voltage (V)			230/400		
Nominal Output Frequency (Hz)			50/60		
Max. AC Output Current (A)	60.5	67	75.5	83.5	96
Peak Output Power	39.6kVA, 60s	44kVA, 60s	49.5kVA, 60s	55kVA, 60s	66kVA, 60s
THDV (with linear load)			3%		
Switching Time (ms)			<10		
Efficiency					
Europe Efficiency	98.20%	98.30%	98.30%	98.30%	98.30%
Max. Efficiency			98.60%		
Battery Charge/Discharge Efficiency			99.00%		
Protection					
Reverse Polarity Protection			Yes		
Over Current / Voltage Protection			Yes		
Anti-islanding Protection			Yes		
AC Short-circuit Protection			Yes		
Leakage Current Detection			Yes		
Ground Fault Monitoring			Yes		
Grid Monitoring			Yes		
Enclosure Protect Level			IP66		
AC/DC surge protection			Type II		
General Data					
Dimensions (W x H x D, mm)			867 x 715 x 306 mm		
Weight (kg)			81kg		
Topology			Transformerless		
Cooling Concept			Intelligent Fan		
Relative Humidity			0-100%		
Operating Temperature Range (°C)			-25 to 60 °C		
Operating Altitude (m)			<4000		
Standby Consumption (W)			<100		
Display & Communication Interfaces		LCD, LED, RS485, CAN, Wi-Fi, GPRS, 4G, Sunspec			
Certification & Approvals	NRS097, G99, EN50549-1, C10/C11, AS4777.2, VDE-AR-N4105, VDE0126, IEC62109-1, IEC62109-2				
EMC	EN61000-6-2, EN61000-6-4				

| Stack-mounted Residential ESS



SAFETY

LFP Battery, Intelligent BMS and protective hardware providing complete protection



ACCURACY

Dynamic SOC calibration



COMPATIBILITY

Suitable for most mainstream inverters



EASY INSTALLATION

Scalable up to 56 packs

Model	AF10000W-HN	AF15000W-HN	AF20000W-HN	AF25000W-HN	AF30000W-HN	AF35000W-HN	AF40000W-HN
Parameter							
Battery Type	LFP						
Number of Connection	2pcs	3pcs	4pcs	5pcs	6pcs	7pcs	8pcs
Total Energy	10.44kWh	15.66kWh	20.88kWh	26.11kWh	31.33kWh	36.55kWh	41.77kWh
Usable Energy	9.92kWh	14.88kWh	19.84kWh	24.81kWh	29.77kWh	34.73kWh	39.69kWh
Max.Parallel Connections	8P						
Voltage	102.4 Vd.c.	153.6 Vd.c.	204.8 Vd.c.	256 Vd.c.	307.2 Vd.c.	358.4 Vd.c.	409.6 Vd.c.
Nominal Charging Voltage	115.2 Vd.c.	172.8 Vd.c.	230.4 Vd.c.	288 Vd.c.	345.6 Vd.c.	403.2 Vd.c.	460.8 Vd.c.
Max. Charging Current	50A						
Nominal Discharging Current	50A						
Discharge Cut-off Voltage	89.6 Vd.c.	134.4 Vd.c.	179.2 Vd.c.	224 Vd.c.	268.8 Vd.c.	313.6 Vd.c.	358.4 Vd.c.
Battery Efficiency	95%						
Battery Protection	Over-current/Over-voltage/Short-circuit/Under-voltage/Over temperature						
Maximum Recommended DOD	95%						
Communication	CAN,RS485						
IP Rating	IP66						
Operating Temperature	-15~50 ℃						
Altitude	≤5,000m						
Humidity	15% ~ 85%RH (No condensation)						
Dimension	(720±2)* (420±2)* (616±3)mm	(720±2)* (420±2)* (766±5)mm	(720±2)* (420±2)* (916±7)mm	(720±2)* (420±2)* (1066±9)mm	(720±2)* (420±2)* (1216±11)mm	(720±2)* (420±2)* (1366±13)mm	(720±2)* (420±2)* (1566±13)mm
Net Weight	(116±3)kg	(163±5)kg	(210±7)kg	(257±9)kg	(304±11)kg	(351±13)kg	(398±13)kg
Heating Unit	51.2V/65W*4						
Certificates	CE-EMC,IEC62619,IEC62477,IEC62040,IEC62100,IEC60068-2-52,IEC60730,UN38.3,MSDS						
Installation	Stacked Installation						

Model AF5000W-HM

Parameter	
Total Energy	5.22 kWh
Usable Energy*	4.96 kWh
Voltage Range	44.8~57.6 Vd.c
Nominal Voltage	51.2 V
Max.Charging Voltage	57.6 V
Max.Continuous Charging Current	50 A
Max.Continuous Discharge Current	50 A
DOD	95%
Dimension ((L*W*H),mm)	(720±2)* (420±2)* (174±3)mm
Net Weight	(47±2)kg
Operating Condition	Indoor or outdoor
Operating Temperature	-15~50 ℃
Humidity	15% ~ 85%RH (No condensation)
Configuration	(8S)2S
Heating Unit	51.2V/65W*4

| Stack-mounted Residential ESS



Support mixing of old and new batteries



Superior Voltage Stability & Regulation



High Efficiency and Extended Runtime



Optimal Battery Performance and Health



Design Flexibility and Compatibility



Enhanced Safety and Protection

Model	AF8000W-HA4	AF16000W-HA4	AF24000W-HA4	AF32000W-HA4
Parameter				
Number of Packs	1pcs	2pcs	3pcs	4pcs
Total Energy	8.03kWh	16.07kWh	24.11kWh	32.15kWh
Usable Energy*	7.63kWh	15.27kWh	22.91kWh	30.55kWh
Charging Voltage Range on HV Side	504~657 Vd.c			
Discharging Voltage Range on HV Side	481.6~657 Vd.c			
Nominal Voltage on HV Side	576			
Nominal Current on HV Side	7A	14A	21A	28A
Voltage Range on LV Side	22.4~29.2Vd.c.			
Nominal Voltage on LV Side	25.6Vd.c.			
Nominal Current on LV Side	156A			
Recommended DOD	95%			
Max.Number of Parallel Connections	4			
Communication	CAN/RS485/WIFI			
Dimension (L*W*H)	(800±2)* (270±2)* (610±3) mm	(800±2)* (270±2)* (950±3) mm	(800±2)* (270±2)* (1290±3) mm	(800±2)* (270±2)* (1630±3) mm
Net Weight	(116±3)kg	(186±5)kg	(256±7)kg	(326±7)kg
Running Environment	Indoor or Outdoor			
Operating Temperature	-15~52°C			
Humidity	15%~85%RH (No condensation)			
Cooling Type	Natural cooling			
WiFi Frequency Range	2412MHz~2472MHz			
Max. WiFi Transmission Power	20dBm			
IP Rating	IP66			
Installation	Stack-mounted			
Power Source	Station-powered			
Heating Unit	18V/10A*2			

*Testing conditions based on temperature 25°C at the beginning of life.
Total Energy/Usable Energy are measured with a standard test method: 0.2C Charge and Discharge.
As per the characteristics of lithium batteries, such parameters as the charge/ discharge current and efficiency listed above are subject to change.

Split Phase Hybrid Storage Inverter

3-9.6 kW



The Afore AF series storage inverters are designed to increase energy independence for homeowners. The power range is from 3.0kW to 9.6kW, compatible with high voltage (80-495V) batteries.

Energy management is based on time-of-use and demand charge rate structures, significantly reduce the amount of energy purchased from public grid.

Thanks for the UPS function (switch time < 10ms), that it enables the crucial loads power on during outages. Additionally, under the backup operation mode, the inverter provides you up to 150% peak output overloading.

The Afore energy storage inverter features Smart Electricity Pricing & Automation, an energy management tool based on real-time electricity pricing strategies. It continuously monitors electricity price fluctuations and dynamically adjusts device operation accordingly. Operating 24/7 fully automatically without the need for manual intervention, it helps users optimize their electricity usage and reduce energy costs.



AI EMS
Electricity Pricing & Automation



Max. 1.5
PV OVERSIZE
1.5 Times PV Oversize



3 MPPT
MPPT CHANNELS
Up to 3 MPPT Channels



<10 ms
UPS FUNCTION
Switch Time < 10ms



PARALLEL
Max.6 Parallel Stacking



INPUT
Support Generator



SPLIT-PHASE
Support Split-phase (120/240Vac) Grid

Support for Time-of-use Optimization

Configurable Operation Modes


AFCI (Optional) & Rapid Shutdown Ready

Build in Anti-feed-in Function


Compact Size and Easy Installation

Smart Monitoring & Remote Firmware Upgrade

For New Storage System:




Optimizing Self-Consumption (on-grid) + Emergency Power Supply (off-grid)



Optimizing Self-Consumption Mode

With home energy storage installed, home owners may also be able to change from a flat rate electricity tariff to a time-of-use tariff. For the areas and regions, where peak shaving can be applied.



Technical Data	AF3K-DH	AF3.6K-DH	AF4K-DH	AF4.6K-DH	AF5K-DH	AF5.5K-DH
PV Input						
Max. Input Power (kW)	4.5	5.4	6.0	6.9	7.5	8.3
Max. PV Voltage (V)	600					
MPPT Range (V)	80 - 550					
Full MPPT Range (V)	110 - 550	135 - 550	150 - 550	170 - 550	185 - 550	200 - 550
Normal Voltage (V)	360					
Startup Voltage (V)	100					
Max. Input Current (A)	15.5 x 2					
Max. Short Current (A)	26.0 x 2					
No. of MPP Tracker / No. of PV String	2 / 2					
Battery Port						
Max. Charge/Discharge Power (kW)	4.5 / 4.5	5.4 / 5.4	6.0 / 6.0	6.9 / 6.9	7.5 / 7.5	8.3 / 8.3
Max. Charge/Discharge Current (A)	50					
Battery Normal Voltage (V)	230					
Battery Voltage Range (V)	80 - 495					
Battery Type	Li-ion / Lead-acid etc.					
AC Grid						
Max Continuous Current (A)	15	17.5	19.5	22.5	24.5	27
Max Continuous Power (kVA)	3.0	3.6	4.0	4.6	5.0	5.5
Nominal Grid Current (A)	12.5 / 14.5	15.0 / 17.4	17.0 / 19.3	19.5 / 22.2	20.9 / 24.1	23.0 / 26.5
Nominal Grid Voltage (V)	211 to 264 @ 240 / 183 to 229 @ 208					
Nominal Grid Frequency (Hz)	60					
Power Factor	1 default (adjustable from 0.8 leading to 0.8 lagging)					
Current THD (%)	< 3					
Gen Input & AC Load Output						
Max. Continuous Current (A)	15	17.5	19.5	22.5	24.5	27
Max. Continuous Power (kVA)	3.0	3.6	4.0	4.6	5.0	5.5
Max. Peak Current (A) (10min)	18.8 / 21.7	22.5 / 26.0	25 / 28.9	28.8 / 33.2	31.3 / 36.1	34.6 / 39.9
Max. Peak Power (kVA) (10min)	4.5 / 4.5	5.4 / 5.4	6.0 / 6.0	6.9 / 6.9	7.5 / 7.5	8.3 / 8.3
Nominal AC Voltage L-L (V)	240 / 208					
Nominal AC Voltage L-N (V)	120 / 104					
Nominal AC Frequency (Hz)	60					
Switching Time (ms)	< 10					
Voltage THD (%)	< 3					
Efficiency						
CEC Efficiency (%)	97.0					
Max. Efficiency (%)	97.6					
PV to Bat. Efficiency (%)	98.1					
Bat. between AC Efficiency (%)	96.8					
Protection						
PV Reverse Polarity Protection	Yes					
Bat. Reverse Polarity Protection	Yes					
Over Current/Voltage Protection	Yes					
Anti-Islanding Protection	Yes					
AC Short Circuit Protection	Yes					
Residual Current Detection	Yes					
Ground Fault Monitoring	Yes					
Insulation Resister Detection	Yes					
PV Arc Detection	Yes					
Rapid Shut Down	Yes					
Protection Degree	NEMA4X					
AC/DC surge protection	Type II					
General Data						
Dimensions (W x H x D)	400 x 600 x 229 mm / 15.7 x 23.6 x 9.0 in					
Weight	25 kg / 55 lbs					
Topology	Tranformerless					
Cooling	Intelligent Fan					
Relative Humidity	0 - 100 %					
Operating Temperature Range	- 25 to 60 °C / - 77 to 140 °F					
Operating Altitude	< 4000 m / < 13123 ft					
Standby Consumption (W)	< 10					
Mounting	Wall Bracket					
Communication with RSD	SUNSPEC					
Display & Communication Interfaces	LCD, LED, RS485, CAN, Wi-Fi, GPRS, 4G, Sunspec					
Certification & Approvals	UL 1741 SA, UL 1741, UL1699B, UL 1998, IEEE1547, IEEE1547A, IEEE1547.1, CSA 22.2 No.107, Rule21, HECO Rule 14					
EMC	FCC part15 CLASS B					

Technical Data	AF6K-DH	AF7K-DH	AF7.6K-DH	AF8K-DH	AF8.6K-DH	AF9.6K-DH
PV Input						
Max. Input Power (kW)	9.0	10.5	11.4	12.0	12.9	15.0
Max. PV Voltage (V)	600					
MPPT Range (V)	80 - 550					
Full MPPT Range (V)	220 - 550	170 - 550	185 - 550	195 - 550	210 - 550	235 - 550
Normal Voltage (V)	360					
Startup Voltage (V)	100					
Max. Input Current (A)	15.5 x 2		15.5 x 3			
Max. Short Current (A)	26.0 x 2		26.0 x 3			
No. of MPP Tracker / No. of PV String	2 / 2		3 / 3			
Battery Port						
Max. Charge/Discharge Power (kW)	9.0 / 9.0	10.5 / 10.3	11.4 / 10.3	11.5 / 10.3	11.5 / 10.3	11.5 / 10.3
Max. Charge/Discharge Current (A)	50					
Battery Normal Voltage (V)	230					
Battery Voltage Range (V)	80 - 495					
Battery Type	Li-ion / Lead-acid etc.					
AC Grid						
Max Continuous Current (A)	29.0	34.0	37	39	41.5	46.5
Max Continuous Power (kVA)	6.0	7.0	7.6	8.0	8.6	9.6
Nominal Grid Current (A)	25.0 / 28.9	29.2 / 33.7	31.7 / 36.6	33.4 / 38.5	35.9 / 41.4	40.0 / 46.2
Nominal Grid Voltage (V)	211 to 264 @ 240 / 183 to 229 @ 208					
Nominal Grid Frequency (Hz)	60					
Power Factor	1 default (adjustable from 0.8 leading to 0.8 lagging)					
Current THD (%)	< 3					
Gen Input & AC Load Output						
Max. Continuous Current (A)	29.0	34.0	37	39	41.5	46.5
Max. Continuous Power (kVA)	6.0	7.0	7.6	8.0	8.6	9.6
Max. Peak Current (A) (10min)	37.5 / 43.3	43.8 / 49.5	47.5 / 49.5	47.9 / 49.5	47.9 / 49.5	47.9 / 49.5
Max. Peak Power (kVA) (10min)	9.0 / 9.0	10.5 / 10.3	11.4 / 10.3	11.5 / 10.3	11.5 / 10.3	11.5 / 10.3
Nominal AC Voltage L-L (V)	240 / 208					
Nominal AC Voltage L-N (V)	120 / 104					
Nominal AC Frequency (Hz)	60					
Switching Time (ms)	< 10					
Voltage THD (%)	< 3					
Efficiency						
CEC Efficiency (%)	97.0					
Max. Efficiency (%)	97.6					
PV to Bat. Efficiency (%)	98.1					
Bat. between AC Efficiency (%)	96.8					
Protection						
PV Reverse Polarity Protection	Yes					
Bat. Reverse Polarity Protection	Yes					
Over Current/Voltage Protection	Yes					
Anti-Islanding Protection	Yes					
AC Short Circuit Protection	Yes					
Residual Current Detection	Yes					
Ground Fault Monitoring	Yes					
Insulation Resister Detection	Yes					
PV Arc Detection	Yes					
Rapid Shut Down	Yes					
Protection Degree	NEMA4X					
AC/DC surge protection	Type II					
General Data						
Dimensions (W x H x D)	400 x 600 x 229 mm / 15.7 x 23.6 x 9.0 in					
Weight	25 kg / 55 lbs					
Topology	Tranformerless					
Cooling	Intelligent Fan					
Relative Humidity	0 - 100 %					
Operating Temperature Range	- 25 to 60 °C / - 77 to 140 °F					
Operating Altitude	< 4000 m / < 13123 ft					
Standby Consumption (W)	< 10					
Mounting	Wall Bracket					
Communication with RSD	SUNSPEC					
Display & Communication Interfaces	LCD, LED, RS485, CAN, Wi-Fi, GPRS, 4G, Sunspec					
Certification & Approvals	UL 1741 SA, UL 1741, UL1699B, UL 1998, IEEE1547, IEEE1547A, IEEE1547.1, CSA 22.2 No.107, Rule21, HECO Rule 14					
EMC	FCC part15 CLASS B					

Single Phase
PV String Inverter
1-3 kW



Single Phase
PV String Inverter
3-6 kW



Single Phase
PV String Inverter
7-10 kW



■ Technical Data	HNS1000TL-1	HNS1500TL-1	HNS2000TL-1	HNS2500TL-1	HNS3000TL-1	HNS3000TL	HNS3600TL	HNS4000TL	HNS5000TL	HNS6000TL	HNS7000TL	HNS8000TL	HNS9000TL	HNS10000TL
PV Input Data														
Max. DC Power (W)	1500	2250	3000	3750	4200	4500	5400	6000	7000	8400	9800	11200	12600	14000
Max. DC Voltage (V)	500	500	500	500	500	600	600	600	600	600	600	600	600	600
MPPT Voltage Range (V)	50 - 500	50 - 500	50 - 500	50 - 500	50 - 500	70 - 550	70 - 550	70 - 550	70 - 550	70 - 550	70 - 550	70 - 550	70 - 550	70 - 550
MPPT Full Power Voltage Range (V)	70 - 500	110 - 500	145 - 500	180 - 500	220 - 500	110 - 550	130 - 550	145 - 550	180 - 550	220 - 550	220 - 550	220 - 550	220 - 550	220 - 550
Rated Input Voltage (V)	360					360					360			
Start-up Voltage (V)	50					70					70			
Max. Input Current (A)	14					14 x 2					14+26		26+26	
Max. Short Current (A)	18					18 x 2					18+35		35+35	
No. of MPP Tracker / No. of PV String	1/1					2/2					2/3		2/4	
Input Connector Type	MC4					MC4					MC4			
AC Output Data														
Max. Output Power (VA)	1100	1650	2200	2750	3300	3300	3960	4400	5500	6600	7700	8800	9900	11000
Nominal Output Power (W)	1000	1500	2000	2500	3000	3000	3600	4000	5000	6000	7000	8000	9000	10000
Max. Output Current (A)	6	9	12	13	15	15	17.5	20	24	28.7	33.6	38.3	45	50
Nominal Output Voltage (V)	L/N/PE, 220Vac, 230Vac, 240Vac					L/N/PE, 220Vac, 230Vac, 240Vac					L/N/PE, 220Vac, 230Vac, 240Vac			
Grid Voltage Range	180Vac-276Vac (According to local standard)					180Vac-276Vac (According to local standard)					180Vac-276Vac (According to local standard)			
Nominal Output Frequency (Hz)	50/60					50/60					50/60			
Grid Frequency Range	45-55Hz/54-66Hz (According to local standard)					45-55Hz/54-66Hz (According to local standard)					45-55Hz/54-66Hz (According to local standard)			
Output Power Factor	1 default (adjustable from 0.8 leading to 0.8 lagging)					1 default (adjustable from 0.8 leading to 0.8 lagging)					1 default (adjustable from 0.8 leading to 0.8 lagging)			
Output Current THD	<3%					<3%					<3%			
Efficiency														
Max. Efficiency	97.50%	97.80%	98.10%	98.10%	98.13%	98.20%	98.20%	98.20%	98.20%	98.20%	98.20%	98.20%	98.32%	98.40%
Euro Efficiency	96.60%	96.70%	96.80%	97.23%	97.56%	97.80%	97.82%	97.85%	97.90%	97.92%	97.95%	98.00%	98.00%	98.10%
Protection														
PV Reverse Polarity Protection	YES					YES					YES			
PV Insulation Resistance Detection	YES					YES					YES			
AC Short Circuit Protection	YES					YES					YES			
AC Over Current Protection	YES					YES					YES			
AC Over Voltage Protection	YES					YES					YES			
Anti-Islanding Protection	YES					YES					YES			
Residual Current Detection	YES					YES					YES			
Over Temperature Protection	YES					YES					YES			
Integrated DC switch	YES					YES					YES			
Surge Protection	Integrated (Type III)					Integrated (Type III)					Integrated (Type III)			
Smart IV Curve Scanning	YES					YES					YES			
Quick Arc Fault Circuit interruption	Optional					Optional					Optional			
General Data														
Dimensions (W x H x D, mm)	280 x 260 x 116					360 x 358 x 142					370 x 535 x 192			
Weight (kg)	6					10					17	18		
Protection Degree	IP65					IP66					IP66			
Enclosure Material	Aluminum					Aluminum					Aluminum			
Ambient Temperature Range (°C)	-25 - + 60					-25 - + 60					-25 - + 60			
Humidity Range	0 - 100%					0 - 100%					0 - 100%			
Topology	Transformerless					Transformerless					Transformerless			
Communication Interface	RS485 / WiFi / Wire Ethernet / GPRS (optional)					RS485 / WiFi / Wire Ethernet / GPRS (optional)					RS485 / WiFi / Wire Ethernet / GPRS (optional)			
Cooling Concept	Convection					Convection					Convection	Intelligent fan cooling		
Night Power Consumption (W)	<0.2	<0.2	<1	<1	<1	<1					<1			
Max. Operation Altitude (m)	4000					4000					4000			
Certifications and Standards														
EMC Standard	EN/IEC 61000-6-2, EN/IEC 61000-6-3, EN61000-3-2, EN61000-3-3						EN/IEC 61000-6-2, EN/IEC 61000-6-3, EN61000-3-2, EN61000-3-3, EN61000-3-11, EN61000-3-12							
Safety Standard	IEC 60068, UL1741, EN62109						IEC 60068, UL1741, EN62109							
Grid-connection	IEEE1547, CSA C22, EN50549, VDE4105, VDE0126, RD1699, ABNT NBR16149 & 16150, AS4777.2, NB/T32004, G98, IEC61727						IEEE1547, CSA C22, EN50549, VDE4105, VDE0126, RD1699, ABNT NBR16149 & 16150, AS4777.2, NB/T32004, G99, IEC61727							

Three Phase PV String Inverter

3-25 kW



Smart | Safety | Efficient

The Afore BNT Series Three-phase string inverters are designed for residential and small commercial PV system applications, rating from 3kW to 25kW. All models have unibody housings with aluminum structure which is anodized, increasing durability and effectively prevents corrosion. Equipped with external inductors, the unibody housings can ensure efficient heat dissipation, which significantly improves the reliability and extends the life of the inverters.

Communication implements are via the Wi-Fi module (can be changed to Ethernet / GPRS). Check the system status anytime and anywhere via online portal or APP.

Quick Arc Fault circuit interruption (Optional)
 WIFI standard
 Compact design
 Multiple intelligent protections
 Compatible with bifacial modules
 String level monitoring



MPPT Range
Wide MPPT Range



PV OVERSIZE
1.5 Times PV Oversize



DC 1100V
Max. DC 1100V



UNIBODY
One-piece
Aluminum Housing



PROTECTION
Build-in SPD Type II



SMART
Smart IV Curve Scanning



UPDATE
Remote Firmware Update

Technical Data	BNT003KTL	BNT004KTL	BNT005KTL	BNT006KTL	BNT008KTL	BNT010KTL
PV Input Data						
Max. DC Power (W)	5100	6000	7500	9000	12000	15000
Max. DC Voltage (V)	1100					
MPPT Voltage Range (V)	150 - 1000					
MPPT Full Power Voltage Range (V)	200 - 850		250 - 850	300 - 850	500 - 850	
Rated Input Voltage (V)	620					
Start-up Voltage (V)	150					
Max. Input Current (A)	15 x 2					
Max. Short Current (A)	25 x 2					
No. of MPP Tracker / No. of PV String	2/2					
Input Connector Type	MC4					
AC Output Data						
Max. Output Power (VA)	3300	4400	5500	6600	8800	11000
Nominal Output Power (W)	3000	4000	5000	6000	8000	10000
Max. Output Current (A)	5.3	7	8.5	10.5	13.5	17
Nominal Output Voltage (V)	3P+N+PE /3P+PE 230/400					
Grid Voltage Range	260Vac-519Vac (according to local standard)					
Nominal Output Frequency (Hz)	50/60					
Grid Frequency Range	45-55Hz/55-65Hz(according to local standard)					
Output Power Factor	1 default (adjustable from 0.8 leading to 0.8 lagging)					
Output Current THD	<3%					
Efficiency						
Max. Efficiency	98.30%					98.70%
Euro Efficiency	97.61%	97.65%	98.00%	98.05%	98.23%	
Protection						
PV Reverse Polarity Protection	YES					
PV Insulation Resistance Detection	YES					
AC Short Circuit Protection	YES					
AC Over Current Protection	YES					
AC Over Voltage Protection	YES					
Anti-Islanding Protection	YES					
Residual Current Detection	YES					
Over Temperature Protection	YES					
Integrated DC switch	YES					
Surge Protection	Integrated (Type II)					
Smart IV Curve Scanning	YES					
Quick Arc Fault Circuit Interruption	Optional					
General Data						
Dimensions (W x H x D, mm)	370 x 535 x 192					
Weight (kg)	16					
Protection Degree	IP66					
Enclosure Material	Aluminum					
Ambient Temperature Range (°C)	-25 to 60					
Humidity Range	0 -100%					
Topology	Transformerless					
Communication Interface	RS485 / WiFi / Wire Ethernet / GPRS (optional) / Sunspec					
Cooling Concept	Convection			Intelligent fan cooling		
Night Power Consumption (W)	<1					
Max. Operation Altitude (m)	≤4000					
Certifications and Standards						
EMC Standard	EN/IEC 61000-6-2, EN/IEC 61000-6-3, EN61000-3-2, EN61000-3-3					
Safety Standard	IEC 60068, UL1741, EN62109					
Grid-connection	IEEE1547, CSA C22, EN50549, VDE4105, VDE0126, RD1699, ABNT NBR16149 & 16150, AS4777.2, NB/T32004, G98, IEC61727					

Technical Data	BNT012KTL	BNT013KTL	BNT015KTL	BNT017KTL	BNT020KTL	BNT025KTL
PV Input Data						
Max. DC Power (W)	18000	19500	22500	25500	30000	37500
Max. DC Voltage (V)	1100					
MPPT Voltage Range (V)	150 - 1000					
MPPT Full Power Voltage Range (V)	500 - 850					
Rated Input Voltage (V)	620					
Start-up Voltage (V)	150					
Max. Input Current (A)	15 x 2	20 + 32	32 x 2			
Max. Short Current (A)	25 x 2	30 + 48	48 x 2			
No. of MPP Tracker / No. of PV String	2/2	2/3	2/4			
Input Connector Type	MC4					
AC Output Data						
Max. Output Power (VA)	13200	14300	16500	18700	22000	27500
Nominal Output Power (W)	12000	13000	15000	17000	20000	25000
Max. Output Current (A)	21.5	22	27	30	32	40
Nominal Output Voltage (V)	3P+N+PE /3P+PE 230/400					
Grid Voltage Range	260Vac-519Vac (according to local standard)					
Nominal Output Frequency (Hz)	50/60					
Grid Frequency Range	45-55Hz/55-65Hz(according to local standard)					
Output Power Factor	1 default (adjustable from 0.8 leading to 0.8 lagging)					
Output Current THD	<3%					
Efficiency						
Max. Efficiency	98.70%				98.75%	
Euro Efficiency	98.23%				98.35%	
Protection						
PV Reverse Polarity Protection				YES		
PV Insulation Resistance Detection				YES		
AC Short Circuit Protection				YES		
AC Over Current Protection				YES		
AC Over Voltage Protection				YES		
Anti-Islanding Protection				YES		
Residual Current Detection				YES		
Over Temperature Protection				YES		
Integrated DC switch				YES		
Surge Protection	Integrated (Type II)					
Smart IV Curve Scanning	YES					
Quick Arc Fault Circuit Interruption	Optional					
General Data						
Dimensions (W x H x D, mm)	370 x 535 x 192					
Weight (kg)	16	17	19			
Protection Degree	IP66					
Enclosure Material	Aluminum					
Ambient Temperature Range (°C)	-25 to 60					
Humidity Range	0 -100%					
Topology	Transformerless					
Communication Interface	RS485 / WiFi / Wire Ethernet / GPRS (optional) / Sunspec					
Cooling Concept	Intelligent fan cooling					
Night Power Consumption (W)	<1					
Max. Operation Altitude (m)	≤4000					
Certifications and Standards						
EMC Standard	EN/IEC 61000-6-2, EN/IEC 61000-6-3, EN61000-3-2, EN61000-3-3, EN61000-3-11, EN61000-3-12					
Safety Standard	IEC 60068, UL1741, EN62109					
Grid-connection	IEEE1547, CSA C22, EN50549, VDE4105, VDE0126, RD1699, ABNT NBR16149 & 16150, AS4777.2, NB/T32004, G99, IEC61727					

Three Phase PV String Inverter

30-60 kW



The Afore BNT Series Three-phase string inverters are designed for commercial and power plant PV system applications, rating from 30kW to 60kW. All models with aluminum housing which is anodized, increasing durability and effectively prevents corrosion. Equipped with external inductors, ensure efficient heat dissipation, which significantly improves the reliability and extends the life of the inverters.

The inverter menu is activated by sensor touch buttons. Communication implements are via the Wi-Fi module (which can be changed to Ethernet / GPRS). Check the system status anytime and anywhere via online portal or APP.

Max.
20A

MAX. 20Adc
String Current Up To 20A

Max.
1.5

PV OVERSIZE
Max. 1.5 Time
PV Oversize Input

PROTECTION
Multiple Intelligent
Protections

ANTI-FLOW
Anti-Feed-in Function

Wi-Fi
Wi-Fi Standard,
Ethernet/GPRS Optional

CONFIGURATION
Quick & Easy
Config. via Wi-Fi

MODBUS
MODBUS
Communication Ready

MPPT efficiency > 99.9%

Intelligent Temperature Control System

Active and reactive power compensation, adjust power factor

IP 68 Cooling Fan

Type II DC & AC lightning protection

AC output 1.1x continuous operation

Technical Data	BNT030KTL	BNT036KTL	BNT040KTL	BNT050KTL	BNT060KTL
PV Input Data					
Max. DC Power (W)	45000	54000	60000	75000	90000
Max. DC Voltage (V)	1100				
MPPT Voltage Range (V)	200 -1000				
MPPT Full Power Voltage Range (V)	500 - 850				
Rated Input Voltage (V)	620				
Start-up Voltage (V)	200				
Max. Input Current (A)	38 x2	38 x3	40 x3	38 x4	
Max. Short Current (A)	48 x2	48 x3	48 x3	48 x4	
No. of MPP Tracker / No. of PV String	2/5	3/6	3/7	4/8	
Input Connector Type	MC4				
AC Output Data					
Max. Output Power (VA)	33000	39600	44000	55000	66000
Nominal Output Power (W)	30000	36000	40000	50000	60000
Max. Output Current (A)	48	60	65	80	96
Nominal Output Voltage (V)	3P+N+PE /3P+PE 230/400				
Grid Voltage Range	260Vac-519Vac (according to local standard)				
Nominal Output Frequency (Hz)	50/60				
Grid Frequency Range	45-55Hz/55-65Hz (according to local standard)				
Output Power Factor	1 default (adjustable from 0.8 leading to 0.8 lagging)				
Output Current THD	<3%				
Efficiency					
Max. Efficiency	98.50%	98.65%	98.65%	98.80%	99.00%
Euro Efficiency	98.10%	98.20%	98.25%	98.45%	98.50%
Protection					
PV Reverse Polarity Protection	YES				
PV Insulation Resistance Detection	YES				
AC Short Circuit Protection	YES				
AC Over Current Protection	YES				
AC Over Voltage Protection	YES				
Anti-Islanding Protection	YES				
Residual Current Detection	YES				
Over Temperature Protection	YES				
Integrated DC switch	YES				
Surge Protection	Integrated (Type II)				
Smart IV Curve Scanning	YES				
Quick Arc Fault Circuit Interruption	Optional				
General Data					
Dimensions (W x H x D, mm)	450 x 485 x 210	710 x 470 x 236			
Weight (kg)	26	44	51		
Protection Degree	IP66				
Enclosure Material	Aluminum				
Ambient Temperature Range (°C)	-25 to 60				
Humidity Range	0 -100%				
Topology	Transformerless				
Communication Interface	RS485 / WiFi / Wire Ethernet / GPRS (optional) / Sunspec				
Cooling Concept	Intelligent Fan Cooling				
Night Power Consumption (W)	<1				
Max. Operation Altitude (m)	≤4000				
Certifications and Standards					
EMC Standard	EN/IEC 61000-6-2, EN/IEC 61000-6-3, EN61000-3-11, EN61000-3-12				
Safety Standard	IEC 60068, UL1741, EN62109				
Grid-connection	IEEE1547, CSA C22, EN50549, VDE4105, VDE0126, RD1699, ABNT NBR16149 & 16150, AS4777.2, NB/T32004, G99, IEC61727				

Three Phase PV String Inverter

70-110 kW



The Afore BNT Series Three-phase string inverters are designed for commercial and power plant PV system applications, rating from 70kW to 110kW. All models with aluminum housing which is anodized, increasing durability and effectively prevents corrosion. Equipped with external inductors, ensure efficient heat dissipation, which significantly improves the reliability and extends the life of the inverters.

The inverter menu is activated by sensor touch buttons. Communication implements are via the Wi-Fi module (which can be changed to Ethernet / GPRS). Check the system status anytime and anywhere via online portal or APP.



SMART
Intelligent string monitoring,
Smart I-V curve scan



PROTECTION
Type II DC &
AC Lightning Protection



Max. 38A
String Current Up to 38A



>1.5
PV Oversize
>1.5 Time
PV Oversize Input



POWER FACTOR
Active and Reactive
Power Compensation



ANTI-FLOW
Anti-Feed-in Function



IP68 Cooling Fan



Compatible with 210 Solar Panel & bifacial module



Arc Fault Circuit Interrupter (AFCI) (Optional)



AC output 1.1x continuous operation



Multiple Intelligent Protections



Remote firmware upgrade with simple operation




DC side supports "Y" connector



Supports aluminium wire access to reduce cost

Technical Data	BNT070KTL	BNT075KTL	BNT080KTL	BNT090KTL	BNT100KTL	BNT110KTL
PV Input Data						
Max. DC Power (kW)	105	112.5	120	135	150	165
Max. DC Voltage (V)	1100					
MPPT Voltage Range (V)	200 - 1000					
MPPT Full Power Voltage Range (V)	500 - 850					
Rated Input Voltage (V)	620					
Start-up Voltage (V)	300					
Max. Input Current (A)	38 x 6					
Max. Short Current (A)	48 x 6					
No. of MPP Tracker / No. of PV String	6/12					
Input Connector Type	MC4					
AC Output Data						
Max. Output Power (kVA)	77	82.5	88	99	110	110
Nominal Output Power (kW)	70	75	80	90	100	110
Max. Output Current (A)	111	120	127	143	158	159.5
Nominal Output Voltage (V)	3P+N+PE /3P+PE 230/400					
Grid Voltage Range	260Vac-519Vac (according to local standard)					
Nominal Output Frequency (Hz)	50/60					
Grid Frequency Range	45-55Hz/55-66Hz(according to local standard)					
Output Power Factor	1 default (adjustable from 0.8 leading to 0.8 lagging)					
Output Current THD	<3%					
Efficiency						
Max. Efficiency	99.00%					
Euro Efficiency	98.30%			98.40%		
Protection						
PV Reverse Polarity Protection	YES					
PV Insulation Resistance Detection	YES					
AC Short Circuit Protection	YES					
AC Over Current Protection	YES					
AC Over Voltage Protection	YES					
Anti-Islanding Protection	YES					
Residual Current Detection	YES					
Over Temperature Protection	YES					
Integrated DC switch	YES					
Surge Protection	Integrated (Type II)					
Smart IV Curve Scanning	YES					
Quick Arc Fault Circuit Interruption	Optional					
General Data						
Dimensions (W x H x D, mm)	983 x 610 x 318					
Weight (kg)	78					
Protection Degree	IP66					
Enclosure Material	Aluminum					
Ambient Temperature Range (°C)	-25 to 60					
Humidity Range	0 -100%					
Topology	Transformerless					
Communication Interface	RS485 / WiFi / Wire Ethernet / GPRS (optional) / Sunspec					
Cooling Concept	Intelligent fan cooling					
Night Power Consumption (W)	<1					
Max. Operation Altitude (m)	≤4000					
Certifications and Standards						
EMC Standard	EN/IEC 61000-6-2, EN/IEC 61000-6-4, EN61000-3-11, EN61000-3-12					
Safety Standard	IEC 60068, UL1741, EN62109					
Grid-connection	IEEE1547, CSA C22, EN50549, VDE4105, VDE0126, RD1699, ABNT NBR16149 & 16150, AS4777.2, NB/T32004, G99, IEC61727					

Monitoring AI—Electricity Pricing & Automation



Electricity Pricing & Automation is an energy management tool based on real-time electricity price strategy. It monitors electricity price fluctuations in real time and dynamically adjusts the operating status of equipment.

It runs automatically 24 hours a day, 7 days a week without manual intervention. It helps users optimize electricity usage and reduce electricity costs.



Electricity Pricing
& Automation



Failure Alarm



PV Sytem
Information Push



Multiple Systems
In One Account



PC Browser
Andriod And Ios



Real-time/ Historical
Data Monitoring And
Analysis



System Income
Calculation




Wi-Fi / Ethernet / GPRS Data Sticker



Power Plant Data Logger



Zero injection Smart Meter(optional)



Weather Station

Global Projects



All In One Energy Storage System Italy



4kW Tunisia



9.9kW 49.5kW Hiroshima, Japan



60kW 240kW Sri Lanka



5kW Netherlands




10kW Sri Lanka




5kW UK



3883kW Bahrain International Circuit



5kW 30kW Poland



5kW Italy



6kW Italy



6kW Battery: 11kW-h South Africa



9.6kW Battery: 52kW-h 48kW Jamaica



6kW Battery: 10kW-h Vietnam



9.9kW Battery: 85.2kW-h 59.4kW Japan



6kW Battery: 10kW-h Japan



6kW Battery: 8kW-h UK

